

VENETA HD PORCELAIN TILE



VENETA HD PORCELAIN TILE



12" x 24" VENETA ARDESIA HD PORCELAIN TILE

VENETA HD PORCELAIN TILE



13' x 13' VENETA ARDESIA HD PORCELAIN TILE
63-657



2' x 2' VENETA ARDESIA HD PORCELAIN
MOSAICS 63-584



3' x 12' VENETA ARDESIA HD PORCELAIN
BULLNOSE 63-588



12' x 24' VENETA ARDESIA HD PORCELAIN TILE
69-403



13' x 13' VENETA STORMIO HD PORCELAIN TILE
63-658



2' x 2' VENETA STORMIO HD PORCELAIN
MOSAICS 63-585



3' x 12' VENETA STORMIO HD PORCELAIN
BULLNOSE 63-589



12' x 24' VENETA STORMIO HD PORCELAIN TILE
69-404

VENETA HD PORCELAIN TILE




12" x 24" VENETA STORMIO HD PORCELAIN TILE

VENETA HD PORCELAIN TILE



12" x 24" VENETA GRIGIO HD PORCELAIN TILE

VENETA HD PORCELAIN TILE



13" x 13" VENETA GRIGIO HD PORCELAIN TILE
63-659



2" x 2" VENETA GRIGIO HD PORCELAIN
MOSAICS 63-586




3" x 12" VENETA GRIGIO HD PORCELAIN
BULLNOSE 63-590



12" x 24" VENETA GRIGIO HD PORCELAIN TILE
69-405



13" x 13" VENETA ARGENTO HD PORCELAIN TILE
63-660



2" x 2" VENETA ARGENTO HD PORCELAIN
MOSAICS 63-587



3" x 12" VENETA ARGENTO HD PORCELAIN
BULLNOSE 63-591



12" x 24" VENETA ARGENTO HD PORCELAIN TILE
69-406

VENETA HD PORCELAIN TILE



12" x 24" VENETA ARGENTO HD PORCELAIN TILE

VENETA HD PORCELAIN TILE

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE				LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	ARDESIA	STORMIO	GRIGIO	ARGENTO					
13"x 13" VENETA HD PORCELAIN TILE	63-657	63-658	63-659	63-660	42.87	11	12.92	58	671.84
12"x 24" VENETA HD PORCELAIN TILE	69-403	69-404	69-405	69-406	58.12	8	15.50	32	496.00
2"x 2" VENETA HD PORCELAIN MOSAICS	63-584	63-585	63-586	63-587	38.45	10	9.69	48	465.12
3" x 12" VENETA HD PORCELAIN BULLNOSE	63-588	63-589	63-590	63-591	16.46	20	n/a	84	1680 pcs

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	12" x 24"	13" x 13"
THICKNESS		mm – in	9 mm – 11/32"	7.6 mm – 5/16"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	4	4
SCRATCH HARDNESS		(Mohs)	6	6
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 350	≥ 350
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class B – Resistant	Class B – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.60	≥ 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.90	≥ 0.90
DCOF (WET)	ANSI B101.3		≥ 0.70	≥ 0.70
SHADE VARIATION			V2	V2



12" x 24" VENETA STORMIO HD PORCELAIN TILE