



Optional Alzak Finishes

Prescolite has a state-of-the-art spinning and anodizing plant. We can provide a wide variety of optional colors including champagne gold (CG) pewter (PW), wheat (WH), and light wheat (LW) and a variety of optional finish types including semi-specular (SS), specular (blank), or American Matte (MFC).

Example: CFR818UEB-ST492SS



Radio Interference Filter (RIF)

Factory installed filter to suppress radio interference noise that may be conducted through the ballast supply line. Filter is mounted on J-box cover for field wiring to single or twin supply circuits.

To order, specify single (RIF1) or two (RIF2) circuit.

Example: CFR813UEB-ST492A 120V RIF2



Fusing (FSDF)

Fusing ensures that, in the case of a short, only one luminaire goes out rather than all the luminaires on that branch circuit. Fixtures with more than one ballast can be provided with a fuse for each ballast to prevent the other lamps from going out if one ballast should fail. Fusing may be specified for field or factory installation. Fuses are 5 amp with an HLR inline fuse holder and a GMF dual element time delay fuse. To order, specify field (FSDFI) or factory (FSDFA) installed and number of fuses.

Example:
CFR813UEB-ST492A 120V FSDFA



B24 Bar Hangers (B24)

B24 bar hangers provide a secure means of tightly locking down the fixture to standard T-bar grid supports, saving the contractor installation time. Fixed 24" length.

The B24 bar hanger is designed for use with all commercial Prescolite downlights. The bar hangers are compatible with all Prescolite downlights equipped with "C" brackets or universal mounting brackets. Unless otherwise stated, bar hangers are ordered separately.




Sloped Ceiling Adaptors (SCA)

Prescolite manufactures sloped ceiling adaptors for 4", 5", 6", 8", 10", and 12" fixtures from 5° to 35° with flange for dry ceilings or flangeless for wet ceilings. Ceiling cavity recessed depth will vary depending on the slope of the ceiling (contact tech support for more information). SCAs are painted matte white and field installed to the flange of the housing. SCAs are not recommended for use with wall wash trims.


SCA must be assembled to recessed housing at the time of installation. The sloped ceiling adaptor must be installed onto the fixture before installation into the ceiling.

To order, specify ceiling angle (maximum 35°), dry (with flange) or wet (without flange), and fixture.




B6 Bar Hangers (B6)

Slip-strap adjustable bar hangers with nailing holes. Expands to 24" (2 pair per packet).




B7 Bar Hangers (B7)

The fixtures listed below are supplied standard with B7 bar hangers for ceiling joists up to 24" centers. No nails required. LFIL8SH, LFIL9HSQ, LFIL8H




Packet #261 (PKT261)

Converts B7 bar hangers to supports for 2' grid ceiling. On T-bar only, not for H- or Z-bar (4 per packet).




Packet #301 (PKT301)

Converts B9 bar hangers to supports for 2' grids. On T-bar only, not for H- or Z-bar (4 per packet).



Packet #306 (PKT306)

Allows B9 bar hangers to expand to 27" in 90° orientation position (2 per packet).



Packet #384 (PKT384)

Allows use of B6 bar hangers with fixture LFIL11H (4 per packet).



Self-Trim (ST)

Premium self-trim reflectors are standard. Optional painted white self-trim available.

Example: CFR813UEB-ST492WT

Lamps Available

Lamps are available as standard accessory options and shipped separately by Prescolite.