



Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/10/2024 Revision date: 27/08/2024 Supersedes version of: 24/05/2024 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Varnish E 200
UFI : 65JY-T8PG-W00S-NY94
Product code : BDS002193AE
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V.
Touwslagerstraat 1
9240 Zele
Belgium
T +32(0)52/45.60.11, F +32(0)52/45.00.34
hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11
Office hours: 9-17h CET

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Specific target organ toxicity – Single exposure, Category 3, H335
Respiratory tract irritation
Specific target organ toxicity – Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment – Chronic Hazard, H411
Category 2

Full text of H- and EUH-statements: see section 16

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: reaction mass of ethylbenzene and xylene; butanone; ethyl methyl ketone; ethyl acetate; Hydrocarbons, C6, isoalkanes, <5% n-hexane; octhilonone (ISO); 2-octyl-2H-isothiazol-3-one; 2-ethoxy-1-methylethyl acetate; 2PG1EEA

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	25 – 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of ethylbenzene and xylene substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	EC-No.: 905-588-0 REACH-no: 01-2119488216-32	< 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
butanone; ethyl methyl ketone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
ethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC-No.: 931-254-9 REACH-no: 01-2119484651-34	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-ethoxy-1-methylethyl acetate; 2PG1EEA	CAS-No.: 54839-24-6 EC-No.: 259-370-9 EC Index-No.: 603-177-00-8 REACH-no: 01-2119475116-39	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
toluene substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	< 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Terbutryn	CAS-No.: 886-50-0 EC-No.: 212-950-5	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
octhilineone (ISO); 2-octyl-2H-isothiazol-3-one	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	< 0,1	Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0,27 mg/l) Acute Tox. 3 (Dermal), H311 (ATE=311 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=125 mg/kg bodyweight) Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Terbutryn	CAS-No.: 886-50-0 EC-No.: 212-950-5	(3 ≤ C < 100) Skin Sens. 1B; H317
octhilonone (ISO); 2-octyl-2H-isothiazol-3-one	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	(0,0015 ≤ C ≤ 100) Skin Sens. 1A; H317

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- Protective equipment : Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

reaction mass of ethylbenzene and xylene	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
	50 ppm
IOEL STEL	442 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
OEL TWA	221 mg/m ³
	50 ppm
OEL STEL	442 mg/m ³
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Toluène # Tolueen
OEL TWA	77 mg/m ³
	20 ppm
OEL STEL	384 mg/m ³
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

toluene (108-88-3)	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
butanone; ethyl methyl ketone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Butanone
IOEL TWA	600 mg/m ³
	200 ppm
IOEL STEL	900 mg/m ³
	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	2-Butanone # 2-Butanon
OEL TWA	600 mg/m ³
	200 ppm
OEL STEL	900 mg/m ³
	300 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOEL TWA	734 mg/m ³
	200 ppm
IOEL STEL	1468 mg/m ³
	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Belgium - Occupational Exposure Limits	
Local name	Acétate d'éthyle # Ethylacetaat
OEL TWA	734 mg/m ³
	200 ppm
OEL STEL	1468 mg/m ³
	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
dimethyl ether (115-10-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Dimethylether
IOEL TWA	1920 mg/m ³
	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dimethyl ether (115-10-6)

Belgium - Occupational Exposure Limits

Local name	Oxyde de diméthyle # Dimethylether
OEL TWA	1920 mg/m ³
	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

DNEL and PNEC

reaction mass of ethylbenzene and xylene

DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	442 mg/m ³
Acute - local effects, inhalation	442 mg/m ³
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m ³
Long-term - local effects, inhalation	221 mg/m ³

DNEL/DMEL (General population)

Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, oral	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65,3 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0,327 mg/l
PNEC aqua (marine water)	0,327 mg/l
PNEC aqua (intermittent, freshwater)	0,327 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt

PNEC (Soil)

PNEC soil	2,31 mg/kg dwt
-----------	----------------

PNEC (STP)

PNEC sewage treatment plant	6,58 mg/l
-----------------------------	-----------

butanone; ethyl methyl ketone (78-93-3)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	600 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	31 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	106 mg/m ³

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone; ethyl methyl ketone (78-93-3)	
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	55,8 mg/l
PNEC aqua (marine water)	55,8 mg/l
PNEC aqua (intermittent, freshwater)	55,8 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	284,74 mg/kg dwt
PNEC sediment (marine water)	284,7 mg/kg dwt
PNEC (Soil)	
PNEC soil	22,5 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	1000 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	709 mg/l
ethyl acetate (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m ³
Acute - local effects, inhalation	1468 mg/m ³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m ³
Long-term - local effects, inhalation	734 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m ³
Acute - local effects, inhalation	734 mg/m ³
Long-term - systemic effects, oral	4,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m ³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,24 mg/l
PNEC aqua (marine water)	0,024 mg/l
PNEC aqua (intermittent, freshwater)	1,65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,15 mg/kg dwt
PNEC sediment (marine water)	0,115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,2 g/kg food

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)	
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	13964 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5306 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	1301 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1131 mg/m ³
Long-term - systemic effects, dermal	1377 mg/kg bodyweight/day
octhilonone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)	
PNEC (Water)	
PNEC aqua (freshwater)	2,2 µg/l
PNEC aqua (marine water)	0,22 µg/l
PNEC aqua (intermittent, freshwater)	1,22 µg/l
PNEC aqua (intermittent, marine water)	0,122 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	47,5 µg/kg dw
PNEC sediment (marine water)	4,75 µg/kg dw
PNEC (Soil)	
PNEC soil	8,2 µg/kg dw
2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	2366 mg/m ³
Long-term - systemic effects, dermal	103 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	152 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	1420 mg/m ³
Long-term - systemic effects, oral	13,1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	181 mg/m ³
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	2 mg/l
PNEC aqua (marine water)	0,2 mg/l
PNEC aqua (intermittent, freshwater)	2 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	8,2 mg/kg dwt
PNEC sediment (marine water)	0,82 mg/kg dwt

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)

PNEC (Soil)

PNEC soil	0,67 mg/kg dwt
-----------	----------------

PNEC (Oral)

PNEC oral (secondary poisoning)	117 mg/kg food
---------------------------------	----------------

PNEC (STP)

PNEC sewage treatment plant	62,5 mg/l
-----------------------------	-----------

dimethyl ether (115-10-6)

DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation	1894 mg/m ³
--	------------------------

DNEL/DMEL (General population)

Long-term - systemic effects, inhalation	471 mg/m ³
--	-----------------------

PNEC (Water)

PNEC aqua (freshwater)	0,155 mg/l
------------------------	------------

PNEC aqua (marine water)	0,016 mg/l
--------------------------	------------

PNEC aqua (intermittent, freshwater)	1549 mg/l
--------------------------------------	-----------

PNEC (Sediment)

PNEC sediment (freshwater)	0,681 mg/kg dwt
----------------------------	-----------------

PNEC sediment (marine water)	0,069 mg/kg dwt
------------------------------	-----------------

PNEC (Soil)

PNEC soil	0,045 mg/kg dwt
-----------	-----------------

PNEC (STP)

PNEC sewage treatment plant	160 mg/l
-----------------------------	----------

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Butyl-rubber protective gloves.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: DME propelled liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -4 °C (closed cup)
Auto-ignition temperature	: > 200
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: < 20,5 mm ² /s
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,88 g/cm ³ at 20 °C
Relative density	: 0,88 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

Other safety characteristics

VOC content : 675 g/l

Additional information : For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

reaction mass of ethylbenzene and xylene

LD50 dermal rabbit	12126 mg/kg bodyweight
--------------------	------------------------

toluene (108-88-3)

LD50 oral rat	5580 mg/kg bodyweight
---------------	-----------------------

LD50 dermal rabbit	12267 mg/kg bodyweight
--------------------	------------------------

LC50 Inhalation - Rat (Vapours)	30 mg/l/4h
---------------------------------	------------

butanone; ethyl methyl ketone (78-93-3)

LD50 oral rat	> 2193 mg/kg bodyweight
---------------	-------------------------

LD50 dermal	6400 mg/kg bodyweight
-------------	-----------------------

LC50 Inhalation - Rat (Dust/Mist)	> 5000 mg/l/4h
-----------------------------------	----------------

ethyl acetate (141-78-6)

LD50 oral	4934 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rabbit	> 20000 (<) mg/kg bodyweight
--------------------	------------------------------

octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)

LD50 oral rat	125 mg/kg bodyweight
---------------	----------------------

LD50 dermal rabbit	690 mg/kg
--------------------	-----------

2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)

LC50 Inhalation - Rat	> 6,99 mg/l/4h
-----------------------	----------------

dimethyl ether (115-10-6)

LC50 Inhalation - Rat	308,5 mg/l/4h
-----------------------	---------------

LC50 Inhalation - Rat [ppm]	164000 ppm
-----------------------------	------------

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

reaction mass of ethylbenzene and xylene

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

butanone; ethyl methyl ketone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

ethyl acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Hydrocarbons, C6, isoalkanes, <5% n-hexane

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

reaction mass of ethylbenzene and xylene

LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight
----------------------------	----------------------

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

toluene (108-88-3)

LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight
----------------------------	-----------------------

NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight
----------------------------	----------------------

NOAEC (inhalation, rat, vapour, 90 days)	2,355 mg/l air
--	----------------

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

ethyl acetate (141-78-6)

LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight
----------------------------	-----------------------

NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight
----------------------------	----------------------

2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)

NOAEC (inhalation, rat, vapour, 90 days)	≥ 1,266 mg/l air
--	------------------

Aspiration hazard : May be fatal if swallowed and enters airways.

Varnish E 200

Vaporizer	Aerosol
-----------	---------

Viscosity, kinematic	< 20,5 mm ² /s
----------------------	---------------------------

reaction mass of ethylbenzene and xylene

Viscosity, kinematic	0,76 mm ² /s
----------------------	-------------------------

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Viscosity, kinematic	0,46 mm ² /s
----------------------	-------------------------

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

reaction mass of ethylbenzene and xylene

LC50 - Fish [1]	2600 mg/l Oncorhynchus mykiss
-----------------	-------------------------------

toluene (108-88-3)

LC50 - Fish [1]	5,5 mg/l
EC50 - Crustacea [1]	3,78 mg/l
LOEC (chronic)	2,76 mg/l (7 d)
NOEC (chronic)	0,74 mg/l (7 d)
NOEC chronic fish	1,39 mg/l (40 d)

butanone; ethyl methyl ketone (78-93-3)

LC50 - Fish [1]	2993 mg/l
EC50 - Crustacea [1]	308 mg/l
EC50 - Other aquatic organisms [1]	308 mg/l
EC50 72h - Algae [1]	1972 mg/l
EC50 96h - Algae [1]	2029 mg/l

ethyl acetate (141-78-6)

LC50 - Fish [1]	230 mg/l
EC50 - Other aquatic organisms [1]	717 mg/l Daphnia magna (Water flea)
NOEC (chronic)	2,4 mg/l 21 d

Terbutryn (886-50-0)

LC50 - Fish [1]	1,9 mg/l
EC50 - Crustacea [1]	6,4 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	0,0067 mg/l
NOEC chronic fish	0,073 mg/l (28d)

octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)

LC50 - Fish [1]	0,122 mg/l
EC50 - Crustacea [1]	0,107 – 0,32 mg/l
EC50 96h - Algae [1]	0,15 mg/l

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)

LC50 - Fish [1]	140 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	110 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Desmodesmus subspicatus
NOEC (chronic)	≥ 100 mg/l Daphnia magna (21 d)

dimethyl ether (115-10-6)

LC50 - Fish [1]	> 4,1 g/l
EC50 - Crustacea [1]	> 4,4 g/l Daphnia magna (Water flea)
EC50 96h - Algae [1]	154917 mg/l

12.2. Persistence and degradability

Varnish E 200

Persistence and degradability	Not established. No data is available on the degradability of this product.
-------------------------------	---

12.3. Bioaccumulative potential

Varnish E 200

Partition coefficient n-octanol/water (Log Kow)	Not applicable
---	----------------

toluene (108-88-3)

Partition coefficient n-octanol/water (Log Pow)	2,73
---	------

butanone; ethyl methyl ketone (78-93-3)

Partition coefficient n-octanol/water (Log Pow)	0,3
---	-----

ethyl acetate (141-78-6)

Partition coefficient n-octanol/water (Log Pow)	0,7
---	-----

Terbutryn (886-50-0)

Partition coefficient n-octanol/water (Log Pow)	3,74
---	------

octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)

Partition coefficient n-octanol/water (Log Pow)	2,9
---	-----

2-ethoxy-1-methylethyl acetate; 2PG1EEA (54839-24-6)

Partition coefficient n-octanol/water (Log Pow)	0,76
---	------

dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0,07
---	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Varnish E 200

Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII
---------------------------	--

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Additional information : No other effects known
Global warming potential (GWP) : 0.50 (Fluorinated greenhouse gases - (EC) No 2024/573)






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 675 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Comments
2.3	Results of PBT assessment	Modified
12.5	Results of PBT assessment	Modified

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	---

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Varnish E 200

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.