


QX830QT DATA SHEET

Nominal Impedance

Grille Dimensions (WxH)

TECHNICAL SPECIFICATIONS



QX830QT SKU 60647 - Each

Quadratech 1" (25mm) four titanium dome Tweeter Tweeter, Ferrofluid-cooled

4 ohms

Woofer (2) 8" (203mm) Aluminum

Frequency Response 60Hz-24kHz +/-3dB

Recommended Power Range 50 watts minimum: 300 watts maximum

Sensitivity (2.83V/1m) 95dB SPL Crossover 2-way

Average Coverage Angle 92 Degrees Horizontal; 56 Degrees Vertical

Aircraft Marine Grade Aluminum Enclosure

Finishes White Paintable Grille (Paintable By

Request Only)

Cut-Out Dims (WxH) 10.4" x 25.39" (264.16mm x 662.69mm)

Required Mounting Depth (D) 3.875" (98.42mm) Overall Dimensions (WxHxD) 11.1" x 26.09" x 4.125"

(281.94mm x 662.69mm x 104.77mm) 11.1" x 26.09" (281.94mm x 662.69mm)

Environment For indoor use: Available as Marine Grade.

must specify when ordering

3.875" (98.42mm) Mounting Depth **Bottom View**

QX830QT IN-WALL ACCESSORIES

QX830PB

Steel Pre Construction Board | 60188

QX830PBF

MDF Flush-Mount Pre Construction Board | 60187

James by Sonance warrants this product to the original purchaser to be free from defects in materials and workmanship under normal use. Limited Lifetime Warranty applies to indoor installations. Limited Five (5) Year Warranty applies to outdoor or moisture-dense environments (e.g., spas, showers, saunas). Grille is warranted for five (5) years for both indoor and outdoor use. Warranty valid only for products purchased from authorized dealers and installed per manufacturer guidelines. Excludes damage from misuse, accidents, modifications, improper installation, or normal wear. For details or claims, visit sonance.com/company/contact