

ON-WALL SPEAKERS with QUADRATECH DATA SHEET

TECHNICAL SPECIFICATIONS

	OW52QT	OW53QT
Tweeter	(4) 0.75" (19mm) Aluminum Dome Enclosure	(4) 0.75" (19mm) Aluminum Dome Enclosure
Woofer	(1) 5.25" (133mm) Aluminum Cone	(2) 5.25" (133mm) Aluminum Cone
Enclosure	Aircraft Marine Grade Aluminum	Aircraft Marine Grade Aluminum
Crossover	2-Way	2-Way
Frequency Response	70Hz-24kHz +/-3dB	68Hz-24kHz +/-3dB
Impedance	8 ohms nominal	4 ohms nominal
Recommended Power Range	20W - 150W	20W - 200W
Sensitivity (2.83V/1m)	88dB	89dB
Finishes	Gloss White, Satin Black, or Custom	Gloss White, Satin Black, or Custom
Speaker Mounting Depth (D)	3.5" (88.9mm)	3.5" (88.9mm)
Height (H)	12.5" (317.5mm)	20" (508mm)
Width (W)	5.75" (146.05mm)	5.75" (146.05mm)

DIMENSIONS

Shipping Weight



5.75" (146.05mm) Width **OW52QT Front View**



11.2 lbs

3.5" (88.9mm) Mounting Depth **OW52QT Side View**



11.2 lbs

5.75" (146.05mm) Width **OW53QT Front View**



3.5" (88.9mm) Mounting Depth **OW53QT Side View**

LIMITED TEN (10) YEAR WARRANTY* Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance or James Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual. *LIMITED FIVE (5) YEAR WARRANTY FOR MODELS ORDERED AS "MARINE GRADE".

©2025 Sonance. All rights reserved. Sonance and James by Sonance are registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.