



PORTABLE AIR CONDITIONER

8,500 | 10,000 | 12,000 | 13,500 BTU



**3PORT8500A-2
3PORT10000A**



**3PORT12000-2
3PORT13500**

	3PORT8500A-2	3PORT10000A	3PORT12000-2	3PORT13500
UPC CODE	842149003258	842149002497	842149003265	842149002510
COOLING BTU (ashrae)	8,500	10,000	12,000	13,500
COOLING BTU (SACC)	5,000	7,100	8,000	10,000
DOE SACC COVERAGE (sq. ft.)	150	250	450	550
CEER	6.1	7.0	7.2	7.9
ENERGY STAR RATED	—	—	—	—
FAN SPEEDS (Cool/Fan)	2/2	2/2	3/3	3/3
AMPS	7.3	8.1	9.6	11
WATTS	890	920	1095	1250
DECIBELS (Hi/Md/Lo)	53/-/51.5	55.5/-/51.5	54/50/48.9	54.0/52.5/51.5
VENT HOSE LENGTH (in.)	59	59	59	59
TIMER	✓	✓	✓	✓
AUTO-SWING LOUVERS	—	—	✓	✓
UNIT DIMENSION (WxHxD) (in.)	11.75 × 27.25 × 11.5	11.75 × 27.25 × 11.5	16.25 × 27.5 × 12	17.5 × 28.75 × 13.75
PKG. DIMENSION (WxHxD) (in.)	14 × 35 × 13.25	14 × 35 × 13.25	18.25 × 34.25 × 13	19 × 35 × 15.25
CONTAINER QTY. (20' /40' /40' HQ)	232/476/707	232/476/707	178/364/546	146/294/448
WEIGHT (Net/Gross) (lbs.)	50/57.5	50/58	61.5/70	69.75/81.5
REFRIGERANT	R32	R32	R32	R32
CERTIFICATION	UL	UL	CSA	CSA
OUTLET CONFIGURATION	 15A-115V	 15A-115V	 15A-115V	 15A-115V



FOLLOW ME
Portable remote control thermostat feature for total room coverage

FEATURES

- Electronic controls
- Temperature output range of 62°F–86°F (17°C–30°C)
- Bucketless drain system
- Auto restart function
- Easy to install & operate
- Sleep mode
- Easy access washable filter
- Full function remote control
- Easy roll casters
- Variable cooling speeds
- CEC Compliant

SLIDER KIT & QUICK CONNECT VENT HOSE

Included with ALL portable AC units

