


Ren




Colors




Light Grey
VTL RNLG



Medium Grey
VTL RNMG




Taupe
VTL RNTA




Dark Grey
VTL RNDG

Sizes



24" x 48" x 10.3mm Rectified



32" x 32" x 11.5mm Rectified



12" x 24" x 8.4mm Rectified



6" Hex Mosaic

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 47" Rectified	23.62" x 47.24"	10.30mm	Matte/Natural
32" x 32" Rectified	31.50" x 31.50"	11.50mm	Matte/Natural
12" x 24" Rectified	11.81" x 23.62"	8.40mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
6" x 6" Hex Mosaics	9.96" x 11.50"	Matte/Natural
2" x 2" Mosaics	11.77" x 11.77"	Matte/Natural
2" x 2" Hex Mosaics	11.73" x 11.85"	Matte/Natural
3" x 24" Bullnose	2.83" x 23.62"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified

Product Characteristics

MATTE/NATURAL	
Breaking Strength (ASTM C648 or ISO 10545-4)	>1650 - >1750
Chemical Resistance (ASTM C650 or ISO 10545-13)	N/A
DCOF	>0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	9
Water Absorption (ASTM C373 or ISO 10545-3)	N/A
Certifications	EPD
Country of Origin	Turkey
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Glazed Color-Body Porcelain

 Made in Turkey

 Ready Ship

 V2 Slight Variation

 DCOF: >0.42

 EPD



Scan QR Code for Product Information and Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

