

FuseLite® Connector, LC, Buffer Tube Fan-Out Single-mode (OS2) UPC

CORNING

Part Number: SOC-LCU-FAN-SM

The FuseLite® Splice-On Connector enables fast, reliable fusion splicing connectivity for local area networks and offers flexibility for repairs and restoration of connectivity.

Available in SC, LC, FC, and ST® Compatible, the FuseLite® Connector provides a reliable connectivity option for applications where fusion splicing may be preferred, such as reflectance-sensitive applications. The FuseLite Connector eliminates the need for splice trays and is compatible with leading fusion splicers in the market.

In applications where fusion splicing is not required, Corning continues to recommend UniCam® High-Performance Connectors, which eliminate the need for capital investments in equipment, or ongoing consumable purchases and installer training. Hand-polished connectors and extremely compact pigtail cassettes for maximum density are also available. Visit www.corning.com/cablesystems or contact Corning Customer Care at 1-800-743-2675 for more information.

Features and Benefits

Broad operating temperature range (-40°C to +75°C)

Utility and flexibility

Factory-polished end face

Consistent optical performance

Fusion splice connectivity


Ideal for reflectance-sensitive applications

Splice protection within connector body

No splice trays required

Available in ribbon and 3 mm cable options

Ideal for cable trunk restoration and repair



FuseLite® Connector, LC, Buffer Tube Fan-Out, Single-mode (OS2) UPC

FuseLite® Connector, LC, Buffer Tube Fan-Out Single-mode (OS2) UPC

CORNING

Specifications

General Specifications

Fiber Category	Single-mode (OS2)
Product Type	Field-Installable Connectors
Compatibility	LC
Corning Logo	Yes
Keyed (security)	No
Technology	Fuse-On

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	Telcordia GR-326-CORE and GR-1081-CORE compliant

Environmental Conditions

Temperature Range, Operation	-40 °C to 40 °C (-40 °F to 104 °F)
------------------------------	------------------------------------

Design - Connector

Connector Type	LC
Housing Color	Blue
Boot Color	Blue
Ferrule Material	Composite
Pinned	No

Optical Specifications - Connector

Polish	UPC
Insertion Loss, Max.	0.3 dB
Reflectance	≤ -55 dB

FuseLite® Connector, LC, Buffer Tube Fan-Out Single-mode (OS2) UPC

CORNING

Optical Specifications - Connector

Insertion Loss, Typical	0.15 dB
-------------------------	---------

Ordering Information

Product Number	SOC-LCU-FAN-SM
EAN Code	4056418150468
Packaging	Individual Pack
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2023 Corning Optical Communications. All rights reserved.