

BLACK DIAMOND®

Project Name: _____

Location: _____

Item #: _____

Qty: _____

Black Diamond Gas Deep Fryer, Liquid Propane, 50 lb, 120K BTU, in Stainless Steel

BDGF-120/LPG



Elevate your commercial kitchen with the Black Diamond Gas Deep Fryer, engineered for durability and high performance. Crafted from stainless steel and cast iron, it boasts a 50-pound capacity, perfect for high-volume cooking. With a temperature range from 200° to 400°F, it ensures optimal frying of various foods. The manual ignition and control system, along with liquid propane compatibility, enhance its functionality. Easy cleaning features make maintenance a breeze.

FEATURES AND CONSTRUCTION

- Constructed with durable stainless steel and cast iron
- Delivers a powerful 120,000 BTUs for efficient frying
- Equipped with 4 burners for versatile cooking options
- Offers a 50 lb capacity for high-volume frying needs
- Includes casters for mobility
- Includes coupling adaptor, gas connection, and uses liquid propane
- Features manual ignition and control for precision cooking
- Temperature range of 200° to 400°F for versatile cooking
- Designed for high-volume commercial kitchen environments
- Perfect for frying a variety of foods like french fries and chicken wings

FRYER ACCESSORIES (OPTIONAL)

- Stainless Steel Cover
- Joiner Strips
- Splash Guard
- Fryer baskets available in a variety of sizes

3RD PARTY APPROVALS



WARRANTY (USA / CANADA)

One (1) Year Limited Warranty on Parts and Labor, Five (5) Year Warranty on Stainless Steel Fry Tank

Contact us for details at 1.877.368.2797



INCLUDED COMPONENTS

- (4) Casters
- (2) Baskets
- (1) Basket Support Rack
- (1) Basket Hanging Plate
- (1) Oil Drainage Extension Pipe

TEMPERATURE


Overall Temperature (Fahrenheit):

- Minimum: 200° - Maximum: 400°F



Black Diamond Gas Deep Fryer, LPG, 50 lb, 120K BTU

BDGF-120/LPG



Gas

Capacity (lbs. of oil)	Temperature Range (Fahrenheit)	BTU / Hour	Assembled Dimensions (in)	Item Weight (lbs)	Shipping Weight (lbs)
50 lbs	200° - 400°	120000	30.24" x 15.51" x 46.29"	145.5	172.0

ADDITIONAL INFORMATION

- Electricity not needed.
- Liquid Propane (LP) or Natural Gas (NG) units available. Field convertible from LP to NG and vice versa.
- Minimum supply pressure is 4" W.C. for natural gas and 10" W.C. for propane.
- Gas powered appliances must always be indoors, under an approved exhaust system with grease removal filters and a fire protection system.

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this document are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.