HUBBELL Wiring Device-Kellems

Straight Blade Devices, Receptacles, RTP, Industrial Grade, 2-Pole 3-Wire Grounding, 30A 250V, 6-30R, Black, Single Pack.

By Hubbell Wiring Device-Kellems Catalog # HBL9330

Straight Blade Devices, Receptacles, RTP, Industrial Grade, 2-Pole 3-Wire Grounding, 30A 250V, 6-30R, Black, Single Pack.



General

Application

Catalog Number Color

EU RoHS Indicator

Environmental Conditions

Environmental Conditions

Horsepower - Maximum

Item Type

Material T

Material - Mounting Hardware Number Of Poles

Operating Temperature

Performance

HBL9330

Noir

Yes

Indoor Dry Unless Protected By

Additional Means

2 Single

Thermoplastic/Composite

Screw Mounting

2-Pole

Maximum continuous 75°C and minimum -40°C without Impact

Electrical - Current Interrupting

- Certified for current interrupting at full rated

current

Electrical - Dielectric Voltage -Withstands 2,000V minimum

Environmental - Flammability -

UL 94 V-0

Environmental - IP Suitability -

IP20

Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)

Mechanical - Product

Identification - Ratings are a permanent part of the device

Mechanical - Terminal

Accommodation - #12 AWG through #4 AWG copper wire

only

Mechanical - Terminal Identification - Terminals identified in accordance with

UL 498 and CSA

Series Extra Heavy Duty

Style Grounding
Type Receptacle
UPC 783585015231

Dimensions

Dimensions 3.28 in x 2.25 in x 2.23 in
Display Size Standard Sized Product

Height 2.23 in Length 3.28 in Weight 0.4 lb Width 2.25 in

Electrical Ratings

Amperage Rating 30 A

Connectivity Back and Side Wired Screw

Terminals

Current / Amperage Rating 30 A
Current Rating 30 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase Voltage Rating 250 V Voltage Rating Description 250 V

Wattage 7500 W

Conductor Related

Number Of Wires 3-Wire Grounding
Wire Size #12 AWG to #4 AWG

Certifications And Compliance

Industry Standard(s) CSA Certified

NEMA® WD-6 Compliant

UL Listed File E2186

Nema Rating 6-30R Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 10 Pallet Quantity 2560

Product Assets

Catalogs - WDK Catalog Full 2024

Warranty - Industrial & Commercial Products



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL9330-SPEC-EN | REV 6/2024