



P604URC1 | HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Home Office Surge Protector P604URC1 prevents spikes in energy caused by storms and electrical power surges from reaching your home office equipment such as laptops, small electronics, and chargers. The P604URC1 provides 500 joules of protection, 6 AC outlets, and a 4-ft. power cord with a right-angle plug. It also has 2 USB ports (2.4 Amp) to quickly charge USB-powered devices.

Features of the P604URC1 include an on/off switch with integrated 15-amp circuit breaker, low-profile cord plug, keyhole mounting slots (back), and damage-resistant construction. This surge suppressor comes with a One-Year Limited Warranty and a \$50,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 500 Joules
- Volts: 125 V
- Circuit breaker: 15 A
- USB ports: 2 (2.4-Amp)
- Plug type: NEMA 5-15P
- Outlet type: NEMA 5-15R
- Outlets: 6 surge-protected
- Power cord: 4 ft
- Color: Black
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$50,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A

OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

P604URC1

HOME OFFICE SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N)
Coax Protection RG6	None
EMI/RFI Filtration	Yes
Maximum Surge Current	15,000 A
Maximum Surge Current H-G	N/A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	N/A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
MANAGEMENT & COMMUNICATIONS	
Indicators	Protected
PHYSICAL	
Color	Black
Cord Management	No
Form Factor	Strip
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	4.72 x 3.45 x 30.99 cm
Physical Dimensions - Width/Height/Depth (mm)	47 x 35 x 310 mm
Physical Dimensions - Width/Height/Depth (in.)	1.86 x 1.36 x 12.2 in.
Weight (kg)	0.36 kg
Weight (lb)	0.80 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	10.8 x 33.99 x 3.51 cm
Shipping Dimensions - Width/Height/Depth (mm)	107.95 x 339.85 x 35.05 mm
Shipping Dimensions - Width/Height/Depth (in.)	4.25 x 13.38 x 1.38 in.
Shipping Weight (kg)	0.45 kg
Shipping Weight (lbs.)	1.00 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 cUL
WARRANTY	
CEG Amount	\$50,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited