



Water Coolers

REMOTE CHILLING PACKAGE

R3, R5

Model

R3 is an efficient 3-gallon chilling unit ideal for installation where it is necessary or desirable to have the cooling unit in an area remote from the drinking fountain.

R5 is an efficient 5-gallon chilling unit ideal for installations where it is necessary or desirable to have the cooling unit in an area remote from the drinking fountain.

Standard Features

- > Waterways are Lead-Free in Materials & Construction
- > May Be Used To Serve Multiple Drinking Fountains
- > Made of Heavy Gauge Steel
- > High-Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Limited 5-Year Warranty

Installation

- > Easy to install
- > Prior to roughing-in, consult local, state and federal codes for proper mounting height.
- > Shipped with complete instructions



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on component parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards. Certified to ANSI/NSF 61 Section 9.



Certified to
NSF/ANSI 61/ Section 9

Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold™ Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Cooling Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
R3**	3.0	3.0	n/a	No	1/5	3.6	250	n/a	n/a	50 Lbs.
R5**	5.0	5.0	n/a	No	1/5	3.6	250	n/a	n/a	50 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.

**Special Export models available, operable on 220-240 volts, 50-60 Hertz. UL and CSA certification not applicable.

Specifications subject to change without notice

OASIS® REMOTE WATER CHILLER MODELS R3, R5

