



TECHNICAL DATA
1/2

CRC CHAIN LUBE

Long term lubricant.

Ref. : 10077



1. GENERAL DESCRIPTION

Gentle foaming action. Long lasting chain lubricant for use on food processing equipment where incidental food contact may occur. Highly resistant to water wash off. The gentle foam assures an excellent penetration and a non dripping action. Good load carrying capabilities and corrosion prevention.

2. FEATURES

- Formulated using only food grade acceptable components.
- Good adhesion on metal surfaces, even at elevated temperatures and high rpm.
- Excellent penetration and lubrication properties.
- Leaves a tenacious, long lasting lubricant film.
- Good load carrying properties.
- Reduces friction and wear.
- Resistant to water wash off.
- Prevents corrosion.
- Operating temperature from -15 °C to +175 °C.
- Virtually odourless and colourless.
- Aerosols are pressurized with non-flammable propellant, giving a gentle foaming action.
- NSF registration :H1 (registration number: 017046)

3. APPLICATIONS

Lubricant for general and food processing industries:

- | | |
|-----------------|-------------------------|
| • Chain drives | • Transfer belts |
| • Open gears | • Forklifts |
| • Wire ropes | • Bearings |
| • Pulleys | • Hoists |
| • Snatch blocks | • Overhead door drivers |
| • Rollers | • Hinges |
| • Conveyors | |
| • Sprockets. | |

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com



