Product specifications

Eaton FRS-R-35

Catalog Number: FRS-R-35

Eaton Bussmann series FRS-R fuse, 35 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 10 sec at 500%, 200 kAIC at 600 V, 20 kAIC at 250 Vdc, Standard, 600 V, 250 Vdc



General specifications

Product Name	**Catalog Number**
Eaton Bussmann series FRS-R fuse	FRS-R-35
UPC	**Product Length/Depth**
051712508353	5.5 in
Product Height	**Product Width**
1.6 in	1.6 in
Product Weight	**Warranty**
0.3 lb	Not Applicable
Compliances	
CE Marked	

Powering Business Worldwide

Electrical rating

Amperage Rating

35 A

Interrupt rating

200 kAIC at 600 Vac

20 kAIC at 250 Vdc

Response time

10 sec at 500%

Voltage rating

600 Vac, 250 Vdc

Physical details

Number of elements

Dual

Packaging type

Standard

General information

Class

Class RK5

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Resources

Catalogs

Low Voltage Branch Circuit Fuse Chapter

Bussmann Full Line Catalog

Compliance information

RoHS Search Tool

Multimedia

Bussmann series Fuseology

Technical service bulletins

Bussmann series FRS-R 600 V Class R up to 60 A fuse data sheet no. 1017

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia