



Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	Finish	Product Weight / Piece (lbs)
P2101	30°	3-1/4" (82.6)	EG	0.58
P2101	30°	3-1/4" (82.6)	HG	0.615
P2101	30°	3-1/4" (82.6)	GR	0.58
P2101	30°	3-1/4" (82.6)	ZD	0.58
P2101	30°	3-1/4" (82.6)	SS	0.58
P2102	22-1/2°	3-5/16" (84.1)	EG	0.58
P2102	22-1/2°	3-5/16" (84.1)	HG	0.615
P2102	22-1/2°	3-5/16" (84.1)	GR	0.58
P2102	22-1/2°	3-5/16" (84.1)	ZD	0.58
P2102	22-1/2°	3-5/16" (84.1)	SS	0.58
P2103	15°	3-5/16" (84.1)	EG	0.58
P2103	15°	3-5/16" (84.1)	HG	0.615
P2103	15°	3-5/16" (84.1)	GR	0.58
P2103	15°	3-5/16" (84.1)	ZD	0.58
P2103	15°	3-5/16" (84.1)	SS	0.58
P2104	7-1/2°	3-5/16" (84.1)	EG	0.55
P2104	7-1/2°	3-5/16" (84.1)	HG	0.615
P2104	7-1/2°	3-5/16" (84.1)	GR	0.58
P2104	7-1/2°	3-5/16" (84.1)	ZD	0.58
P2104	7-1/2°	3-5/16" (84.1)	SS	0.58

Project:

Architect / Engineer:

Date:

Phone:

Contractor:

Address:

Notes:

Approval Stamp: