


## Malleable

### Images

[Download Photo Image](#)[Download Dimensional Image](#)

Dimension A in Inches: 1.342

Dimension B in Inches: 0.638

Dimension C in Inches: 1.715

Dimension D in Inches: 1.722

### Application

45 Degree connector for use with metallic and nonmetallic liquid tight conduit. 1 Inch malleable body with steel nut. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

### Product Information

Material: Malleable Iron

Finish: Zinc Electro-Plate

### Certifications & Codes:

Federal Specification Number: A-A-50552

NEMA Standard: FB-1

UL File Number: E9391, cULus

UL Standard: UL-514B

UNSPSC: 39121420

**Catalog ID:** 452-SLTI**UPC Number:** 78174704452**Description:** Connector, Liquid Tight, 45 Degree, Size 1 Inch, Insulated Throat - 105°C

**Application:** 45 Degree connector for use with metallic and nonmetallic liquid tight conduit. 1 Inch malleable body with steel nut. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

**Trade Size:** 1"**Std Pkg Qty:** 25**Unit Qty:** 5