

CorePro MainsFit (UL Type-B) T8

40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1

CorePro, LEDtube, T8, 2400 mm, 26, 34, 43, Selectable, 3000 K, 3500 K, 4000 K, 5000 K, 6500 K, 3400 lm, 4300 lm, 5200 lm, 50000 hour(s)

CorePro, LEDtube, T8, 2400 mm, 26, 34, 43, Selectable, 3000 K, 3500 K, 4000 K, 5000 K, 6500 K, 3400 lm, 4300 lm, 5200 lm, 50000 hour(s), 126 lm/W, FA8/R17D, Glass, RGO

Product data

General Information	
Cap-Base	FA8/R17D
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LEDtube
Light Technical	
Color Code	3000K/3500K/4000K/5000K/6500K
Beam Angle (Nom)	220 degree(s)
Luminous Flux	3,400 4,300 5,200 lm
Color Designation	3000K/3500K/4000K/5000K/6500K
Correlated Color Temperature (Nom)	Selectable 3000 3500 4000 5000 6500 K
Luminous Efficacy (rated) (Nom)	126 lm/W
Color Consistency	<3
Color rendering index (CRI)	80


LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RGO
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power Consumption	26 34 43
Lamp Current (Nom)	480 mA
Wattage Equivalent	110 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277 V
UL Type	UL Type B

CorePro MainsFit (UL Type-B) T8

Temperature	
T-Case Maximum (Nom)	55 °C
Controls and Dimming	
Dimmable	Limited
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	2,400 mm
Bulb Shape	T8
Net Weight (Piece)	0.430 kg
Approval and Application	
Energy Saving Product	Yes
Approval Marks	RoHS compliance UL certificate DLC compliance
EU RoHS compliant	Yes
Ambient temperature range	-20 to +45 °C



Application Conditions	
can it be used in closed luminaires	Yes
Wireless Technology	Not applicable
Product Data	
Order product name	40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1
Full product name	40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1
Order code	929003815504
Material Nr. (12NC)	929003815504
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677589806
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677589801

Dimensional drawing



Product	D1	D2	A1	A2	A3
40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1		27.9 mm	2,369.8 mm	2,378.7 mm	2,387.8 mm

Photometric data




General uniform lighting - 40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1

Light Distribution Diagram - 40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1


CorePro MainsFit (UL Type-B) T8

Photometric data




Spectral Power Distribution Colour - 40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1


Lifetime




Life Expectancy Diagram



FailureRate




Lumen Maintenance Diagram - 40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1



Lumen Maintenance Diagram - 40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1

CorePro MainsFit (UL Type-B) T8

Lifetime



LifetimeVsTc

