

# SC-DX-GC6

## 6½" In-Ceiling Speakers



### **GRAND STAGE SERIES**

*Experience the best seats in the house with the Grand Stage Series. Explosive dynamics, immersive soundstage, and nuanced realism.*

### **HIGH PERFORMANCE**

**Clarity, Resolution & Dynamics**

Featuring a graphite-injected polypropylene cone woofer and 1" aluminum dome tweeter with vocal contour and tweeter switches. Ideal for hi-fidelity music listening, home theater and media room applications where high performance is critical.



# SC-DX-GC6

## 6½” In-Ceiling Speakers (PAIR)

### Features

- **6 1/2” Carbon Composite Infused Polypropylene Woofer**  
Low Crossover points and a stiff, lightweight, and durable graphite injected cone woofer produces tight bass and transparent midrange for a crystal-clear, dynamic sound.
- **1” Pivoting Aluminum Tweeter**  
Aluminum dome tweeters are lightweight, strong, and respond instantaneously to changes in music or movies.
- **Tilt Tweeter**  
The aimable tweeter allows you to direct sound to the listening area, even when the speaker is mounted in less than ideal locations.
- **Vocal and Tweeter Adjustment Switches**  
Easily adjust tweeter performance or enhance the dialogue in movies.
- **Low Profile Grill**  
A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic—and with a one-step paint process, blends discreetly into any decor.
- **Easy-Grip Tweeter Bridge**  
Installing speakers above your head requires a sturdy grip point and the SpeakerCraft Tweeter bridge ensures you have one. We even protect the tweeter from accidental finger pokes.
- **Precision Tooled Diffusion Baffle**  
Scattered concavities reduce reflection and disperse the sound evenly for a natural room filling experience.
- **Secure Connection**  
All SpeakerCraft speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.
- **Timbre and Performance Matched**  
Expect consistent dynamic and detailed sound in every Grand Stage series speaker.



### Specifications

Woofer Size	6.5” (160mm)
Woofer Construction	Graphite Injected Polypropylene Cone
Tweeter	1” (25mm) Pivoting Aluminum Dome
Frequency Response	50Hz-20kHz
Impedance	8 Ohms
Power Handling	120 Watts
Sensitivity	88 db
Timbre	Timbre-Matched to all Grand Stage Series Speakers
Dimensions	9.625” (237mm) Diameter 3.94” (100mm) Depth
Hole Cutout Dimensions	8.25” (210mm) Diameter
Depth Behind Wall	3.81” (97mm)

Use Pre-Construction Bracket  
Model #: EL-PCB-IC-6



Niceforyou.com

©2023 Nice North America LLC. SpeakerCraft is a registered trademark of Nice North America LLC. All rights reserved.

Rev A - 06/2023

**SPEAKERCRAFT**  
a Nice brand