



Nominal Capacity:	15.0 USG	56.8 lit
Maximum Capacity:	16.5 USG	6.25 lit
Outage:	1.5 USG	5.7 lit
Outage %:	10.0 %	
Nominal O.D.:	14.4 in	365.8 mm
Bottom O.D.:	14.0 in	355.6 mm
Overall Height:	26.1 in	662.9 mm
Mid Panel Height:	15.6 in	396.2 mm
Total Weight:	7.5 lbs	3.4 kg
Body Weight:	6.8 lbs	3.1 kg
Min Wall Thickness:	0.090 in	2.2 mm
Export Cube:	2.95 cub. ft.	0.08 cub.m.
# Across, Std Trailer	6 drums	
Palletizing, Std	45 x 48, 27 drums per pallet	

Regulatory (US):

Test Report #:

UN 1H1/Y1.9/150	P-170
UN 1H1/Y1.8/150	P-198
UN 1H1/Y1.4/150 w/vent	P-171

Regulatory (CAN):

Test Report #:

Not Applicable	
----------------	--

Construction:

Body:	Extrusion blow molded high molecular weight high density polyethylene
Fittings:	2" & 3/4" NPS or one 2" BTR, non-vented or vented.
Special:	Handles – 1 Plastic, hinged

Note: Individual bills of materials may differ according to customer and regulatory requirements. Total drum weight will vary based upon component combination specified.

Filling Temperature:

Maximum filling temperature 160°F. When filled at this maximum temperature, drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.

Stacking/Handling Recommendations:

For non-vented drums, drums may be stacked 4 high (1+3) maximum with pallets between drums. Maximum top load on bottom drums should not exceed 1000 lbs (453.6 kg) each. For vented drums, drums may be stacked 4 high (1+3) maximum with pallets between drums. Maximum top load on bottom drums should not exceed 500 lbs (226.8 kg) each. Pallets should be of good quality and properly sized full double faced construction which provide adequate support for plastic drums. Handle with parrotbeak, side grabber or sling.

Special Notes:

- 1) Volume markers available.
- 2) Recycle symbol embossed on bottom.

DISTRIBUTED BY:



REF NO.:

DWG30618

DESCRIPTION:

15 Gallon HDPE Tight Head Drum

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.