

MEDIUM DUTY REINFORCED WATER-ACTIVATED TAPE



STRENGTH

TAMPER-EVIDENT

DESCRIPTION

3-way fiberglass reinforced natural kraft carton sealing tape manufactured with water-activated adhesive

PRODUCT APPLICATION

- Two strip sealing carton top and bottom.
- Recycled cartons and non-unitized loads.
- Recommended for use on light weight to average cartons up to 30 pounds (14 kg).

PHYSICAL PROPERTIES

Caliper.....	6.3 mils (0.16mm)
MD Tensile	74 lb/in (324 N/25mm)
CD Tensile	26 lb/in (114 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO

2/0	49
2/1	71
5/0	75
15/0	90

MCLAURIN.....	86
---------------	----

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Top Ply.....	23 lb (37 g/m ²) Natural Kraft Paper (virgin fibers)
Bottom Ply	23 lb (37 g/m ²) Natural Kraft Paper (virgin fibers)
Laminating Adhesive	High Melt Index Polypropylene Based Co-Polymer
Water-Activated Adhesive	Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
MD Reinforcement	(1-1-1-1) 75 Fiberglass (per 72mm), 1/2" spacing
CD Reinforcement	(1-1-1) 150 Fiberglass, 1.10" spacing, 44 degree angle

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.