



PowerG D/W Vanishing Contact

PGx303



Intrusion Detection Alerts

Provides instant notifications when doors and windows are opened or closed as a first line of defense during intrusion attempts.



Compact Low-Profile Design

Blends seamlessly into any environment with a slim, sleek casing that fits tight spaces and complements modern décor.



Signal Quality Indicator

Built-in LED indicator helps installers find the optimal mounting location.



Long Battery Life

Powered by a 3V CR2450 lithium battery for up to 6 years of battery life.



PowerG Technology

Delivers secure, long-range, and reliable performance—even in challenging environments.



Easy Installation

Auto-enrollment pull tab make installation quick and efficient.



PowerG

DSC



SPECIFICATIONS

Dimensions (LxWxD)	67 x 31 x 11 mm (2.6 x 1.2 x 0.4 in.)
Battery Type	3V CR2450 lithium battery
Battery Life	Up to 6 years (for typical use)
Weight (including battery)	20 g (0.71 oz)
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Operating Environment	Indoors
Relative Humidity (RH)	Up to 95% non-condensing <i>*UL verified up to a maximum of 85% RH only</i>
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Color Options	White, Brown
Encryption	128-bit AES
Approvals & Certifications	FCC/IC UL/ULC CE EN
Part Number(s)	PG9303 - 912-919 MHz PG8303 - 868 MHz PG4303 - 433 MHz



PowerG

DSC

