HUBBELL Wiring Device-Kellems

Straight Blade Devices, Male Plug, Insulgrip Heavy Duty, Industrial/Commercial Grade, Straight, 2-Pole 3- Wire Grounding, 20A 125V, 5-20P and White

By Hubbell Wiring Device-Kellems Catalog # HBL5366C





General

Application Industrial/Commercial Grade

Catalog Number HBL5366C Color Noir, blanc

EU RoHS Indicator Contact Manufacturer

Horsepower - Maximum

Item TypeInsulgrip PlugMaterialPolycarbonate

Number Of Poles 2-Pole

Operating Temperature Maximum continuous 75°C and

minimum -40°C without Impact

Performance Electrical - Current Interrupting

- Certified for current interrupting at full rated

current

Electrical - Dielectric Voltage - Withstands 2,000V minimum

Environmental - Flammability -

UL 94 HB or better

Environmental - IP Suitability -

IP20

Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)

Mechanical - Terminal

Accommodation - #18-10 AWG. Standed copper wire only Mechanical - Terminal

Identification - Terminals identified in accordance with

UL 498 and CSA

Series Insulgrip®
Style Standard
Type Plug

UPC 783585173955

Dimensions

Dimensions 1.52 in x 1.52 in x 1.96 in

Height 1.96 in
Length 1.52 in
Weight 0.15 lb
Width 1.52 in

Electrical Ratings

Amperage Rating 20 A
Current / Amperage Rating 20 A
Current Rating 20 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase Voltage Rating 125 VAC Voltage Rating Description 125 V

Conductor Related

Number Of Wires 3-Wire

Wire Size #18 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s) CSA Certified to C22.2 No. 42

File 280

Fed. Spec. W-C596G

NEMA® WD-6 Compliant

UL Listed to UL498 File E1706

Nema Rating 5-20P

Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 10 Pallet Quantity 3600

Product Assets

Catalogs - WDK Catalog Full 2024

Warranty - Industrial & Commercial Products



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL5366C-SPEC-EN | REV 6/2024