

D and O Dies



Standard Ultra Range Squeezon Connectors

Seven Connector Series #	Catalog Number	Groove	Standard Conductor			Compact Conductor		Wire Dia. Range		Indents			
			ACSR & Aluminum Alloy	Aluminum or Copper		ACSR	Stranded	Max (in.)	Min	Die	O	WH	Length
				Stranded	Solid								
3	502-82	A	1/0, 2/0	2/0, 3/0	3/0, 4/0	2/0, 3/0	3/0	.470	.398	D	4	2	1-7/8"
		B	s#6, 4, 3, 2	#6, 4, 3, 2, 1-19	#6, 4, 3, 2, 1, 1/0	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1	.332	.162	D3			
5	503-82	A	3/0, 4/0	4/0	250, 266, 300	4/0, 266-16/1	4/0, 250, 266	.563	.480	D	5	2	1-7/8"
		B	#6, 4, 3, 2	#6, 4, 3, 2, 1-19	#6, 4, 3, 2, 1, 1/0	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1	.332	.162	D3			
4	504-82	A	#1, 1/0, 2/0	#1-3, 1/0, 2/0, 3/0	2/0, 3/0, 4/0	1/0, 2/0, 3/0	1/0, 2/0, 3/0	.470	.338	D	5	2	1-7/8"
		B	#1, 1/0, 2/0	#1-3, 1/0, 2/0, 3/0	2/0, 3/0, 4/0	1/0, 2/0, 3/0	1/0, 2/0, 3/0	.470	.338	D3			
6	505-82	A	3/0, 4/0	3/0, 4/0	250, 266, 300	3/0, 4/0, 266-18/1	4/0, 250, 266	.563	.461	D	7	3	2-1/2"
		B	#1, 1/0, 2/0	#1-3, 1/0, 2/0	2/0, 3/0	1/0, 2/0	1/0, 2/0, 3/0	.447	.338	D3			
1	506-82	A	#6, 4, 3, 2	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1, 1/0	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1	.332	.162	0	4	2	1-1/2"
		B	#6, 4, 3, 2	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1, 1/0	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1	.332	.162				
7	507-82	A	3/0, 4/0	3/0, 4/0	250, 266, 300	3/0, 4/0, 266-18/1	4/0, 250, 266	.563	.461	D	7	3	2-1/2"
		B	3/0, 4/0	3/0, 4/0	250, 266, 300	3/0, 4/0, 266-18/1	4/0, 250, 266	.563	.461	D3			
2	508-82	A	#4, 3, 2, 1, 1/0	#3-3, 2, 1, 1/0, 2/0	#1, 1/0, 2/0, 3/0	#2, 1, 1/0, 2/0	#2, 1, 1/0, 2/0	.419	.250	0	5	2	1-3/4"
		B	#6, 4, 3, 2	#6, 4, 3, 2, 1-19	#6, 4, 3, 2, 1, 1/0	#6, 4, 3, 2, 1	#6, 4, 3, 2, 1	.332	.162				