

SP-24

Hydraulic Operated Remote Cutting Head

Specifications

Output	7.8 Ton
Weight	6 lbs.
Length	11"
Jaw Opening	.9"

Capacities

Wire Ropes	22mm, 7/8"
Soft Steel Bolts	20mm, 3/4"
Rebar, Ground & Anchor Rod	16mm, 5/8"
Cu & Al Wire	22mm, 7/8"
ACSR	22mm, 7/8"
Standard Guy Wire	16mm, 5/8"
Chain	Do not Cut
Comm. Cables	Do Not Cut
Lead Sheath Cables	Do Not Cut

Feature

- Lightweight and Portable
- Operate from Any 10,000 psi Hydraulic Source
- Works in Any Position



The **SP-SERIES** remote head units connect to any 10,000 psi, high pressure, hydraulic pumping system. Choose from seven different models of production cutters, to cut costs and efforts. A 3/8" screw-type male coupler is supplied with each tool. Huskie Tools remote cutters have a hinged head which can be opened for easy cable or bar insertion. The movable blade advances in a shear fashion, to cut the material cleanly. When the cutting pressure is relieved an internal ram spring retracts the blade. The guillotine cutting style was chosen over scissor type cutting because of its powerful output force, larger cable capacities, compact size and reliability.

All tools can be used under water, consult factory for specific applications.