

PRODUCT CODE **5515/34.25-G4/AS-11**

## DRUMSAVER™ INSERT FOR STEEL DRUMS

**PRODUCT DESCRIPTION:** The anti-stat version of the popular 5515/34.25-G4 insert, is also a straight-sided, seamless, vacuum-formed insert for 55-gallon open-head steel drums. It is molded from FDA-approved low-density polyethylene. A contoured lip snaps over the top bead to prevent leakage between the insert and the drum wall, while also providing easy drum closure using a standard ring and bolt or lock assembly.

### Insert Specifications

#### MATERIAL USED

Low-density polyethylene

#### INSERT DIMENSIONS

Diameter: 22.5" (+0.25"/-0")

Height: 34.25" (+/-0.125")

Average thickness: 15 mil (+/-10%)

#### WEIGHT

1.55 lbs. (+/-10%)

#### SIDE-WALL DESIGN

Straight sided

#### TEMPERATURE PARAMETERS

High (momentary): 175° (195°) F

Low: -40° F

#### ANTI-STAT

Standard: MIL-B-81705-C

Resistivity rating: 10<sup>11</sup> Ω/Sq. typical

### Packaging Specifications

#### CARTON WEIGHT

36 lb.

#### CARTON DIMENSIONS

Length: 35"

Width: 21"

Height: 15"

#### QUANTITY/CASE

20

#### PACKAGING STYLE

Folded

ANTI-STAT LINERS CONTAIN AN INTERNAL ANTI-STAT AGENT THAT IS INTENDED AS AN AID TO REDUCTION OF STATIC BUILD-UP. THEY ARE NOT DESIGNED AS, AND SHOULD NOT BE USED AS, THE PRIMARY CONTROLLER OF STATIC ELECTRICITY IN A PROCESS. ANTI-STAT LINERS SHOULD NOT BE USED IN ELECTRO-STATIC COATING SYSTEMS OR OTHER HIGHLY VOLATILE AREAS. PLEASE CONSULT YOUR SAFETY ENGINEER, SAFETY CONSULTANT, OR CDF IF THERE IS ANY QUESTION AS TO APPROPRIATENESS OF USE.

**TYPICAL APPLICATIONS:** Ideal for drums using follower plates, or users who prefer a straight-sided insert. It is perfect for mixing, pumping and storing all liquids, powders and pastes that can be contained in low-density polyethylene.

DISTRIBUTED BY:



REF NO.:

DWG50019

DESCRIPTION:

55 Gallon 15 mil LDPE Drumsaver Insert, Straight Sides

#### DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.