




# Location:



1-3170VT-H401-V  
 Visu-Temp® Tub/Shower/Hand Shower System  
**Specification Submittal**



Model Numbers	Feature Highlights
<input type="checkbox"/> <b>1-3170VT-H401-V</b> Visu-Temp® Tub/Shower/Hand Shower System	<ul style="list-style-type: none"> <li>• Visu-Temp® Pressure-Balancing mixing valve with Clear-Vue™ thermometer</li> <li>• Adjustable stop screw to limit handle turn</li> <li>• Lever diverter with volume control for shower head, hand shower and tub spout</li> <li>• Single mode showerhead with arm and flange</li> <li>• Tub spout</li> <li>• Single mode wall/hand shower with flexible 5' metal hose</li> <li>• Dual checks for backflow protection</li> <li>• Wall connection and flange</li> <li>• Cradle for hand shower mounting</li> <li>• Standard flow rate 2.0 gpm (7.6 L/min)</li> </ul>
Options/ Modifications	
<input type="checkbox"/> <b>1.5</b> <b>1.5 gpm (5.7 L/min) flow restrictor</b> <input type="checkbox"/> <b>STN</b> <b>Satin Nickel finish</b> <input type="checkbox"/> <b>X</b> <b>Integral service stops—allows water shut-off at valve for service</b> <input type="checkbox"/> <b>X-3/4</b> <b>3/4" valve to increase flow approximately 20%</b> <input type="checkbox"/> <b>X-CHKS</b> <b>Integral check stops—for use in installations where a positive shut-off device is used downstream of mixing valve</b> <input type="checkbox"/> <b>NS</b> <b>Non-shared diverter valve</b> <input type="checkbox"/> <b>QD</b> <b>Quick disconnect</b> <input type="checkbox"/> <b>TRM</b> <b>Trim only</b>	
<p><b>Note:</b> Append appropriate -suffix to model number.</p>	Warranty
Compliance	<p><b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations.  <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.</p> 
<p>- ASME A112.18.1/CSA B125.1</p> 	

## Architectural/ Engineering Specification

Symmons Visu-Temp Tub and Shower and Hand Shower System \_\_\_\_\_ Includes Visu-Temp Pressure-Balancing mixing valve with Clear-Vue™ thermometer, Adjustable stop screw to limit handle turn, Lever diverter with volume control for shower head, hand shower and tub spout, Single mode showerhead with arm and flange, Tub spout, Single mode wall/hand shower with flexible 5' metal hose, Dual checks for backflow protection, Wall connection and flange, Cradle for hand shower mounting, Standard flow rate 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "STN - Satin Nickel finish", "X - Integral service stops—allows water shut-off at valve for service", "X-3/4 - 3/4" valve to increase flow approximately 20%", "X-CHKS - Integral check stops—for use in installations where a positive shut-off device is used downstream of mixing valve", "NS - Non-shared diverter valve", "QD - Quick disconnect", "TRM - Trim only".

**Dimensions**
