Welding Cable, 600V 105C, EPDM

Welding Cable
EPDM Jacket
105°C - 600 Volt

Flexible and Portable Cord



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Fully annealed stranded bare copper, class K stranding

Category Jacket Description:

- Black premium-grade Ethylene Propylene Diene Monomer (EPDM) 03 = Red jacket 04 = Green Jacket

Applications:

- Secondary voltage resistance welding leads
- Power supply applications not exceeding 600 volts AC

Standards:

- RoHS compliant
- Non-UL/CSA Class K

PART NUMBER TABLE						
Part#	**Gauge**	**Conductors**	**Stranding**	**Outside Diameter Inches**	**Material Weight (Lbs./M')**	**Material Weight (KG/KM)**
B20601	6	1	259/30	0.38	135	200
B20401	4	1	374/30	0.4	172	255
B20201	2	1	625/30	0.465	260	386
B20101	1	1	778/30	0.495	317	471
B21/001	1/0	1	990/30	0.56	400	595
B22/001	2/0	1	1248/30	0.615	487	724
B23/001	3/0	1	1586/30	0.67	605	900
B24/001	4/0	1	2054/30	0.75	827	1230
B225001	250	1	2496/30	0.83	976	1452
B235001	350	1	3432/30	0.96	1338	1991
B250001	500	1	5054/30	1.2	1995	2968

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 ™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC