

3M™ Polyurethane Protective Tape 8560

Product Description

3M™ Polyurethane Protective Tape 8560 (indoor grade) is made from an abrasion-resistant polyurethane elastomer that resists puncture, tearing, abrasion, and erosion. 3M 8560 Tape provides a simple, easy, and fast method of protecting a surface from corrosion, abrasion, and minor impact damage. 3M 8560 Tape is constructed with a pressure-sensitive, natural rubber adhesive protected with an easy-release polyester liner.

3M 8560 Tape is a transparent tape available with a polyester liner only.

Typical Physical Properties and Performance Characteristics

Notes: 1) The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

2) ASTM = American Society for Testing and Material.

3) Metric values are listed in parenthesis.

A. Dimensions

Approximate Applied Thickness:*	0.012 inch (0.30 mm) Film 0.002 inch (0.06 mm) Adhesive 0.014 inch (0.36 mm) = Total thickness
Standard Roll Length:	36 yd (32.9 m)
Available Widths:	Minimum 1/4 inch Maximum 48 inches (0.625 cm to 122 cm)
Approximate Weight:*	0.82 lb/yd ² (447 g/m ²)

*Excludes the polyester liner that is removed from the tape prior to application.

B. Typical Physical Properties and Performance Characteristics

Property	Test Method	Units	Typical Value
Tensile Strength @ Break:	ASTM D882	lb/in (N/100 mm)	75 (1313)
Elongation % @ Break:	ASTM D882	%	400
Peel Adhesion @ 70°F (21°C) to:			
Plate Glass			92 (100)
Anodized Aluminum	ASTM D3330 Method A 24 hour dwell	oz/in (N/100 mm)	29 (31)
Acrylic Enamel Paint			32 (35)
Mil-P-23377 Epoxy Primer			43 (46)

Safety and Regulatory

- 3M™ Polyurethane Protective Tape is **100%** solids and contains no hazardous air pollutants (HAPs), volatile organic components (VOCs). Respiratory protection is not required under normal use conditions.
- Polyurethane Protective Tape meets US Federal and California regulations for landfillable materials.
- Packaging materials meet US Federal and California regulations for landfillable materials and are recyclable or reusable.
- This product is considered to be an article that does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.



Shipping and Storage

No special/hazardous labeling or packaging required and no regulations for air, ground or water shipment for this product.

Keep film in a clean area, away from excessive moisture and out of direct sunlight. Store rolls in the shipping carton. Return partially used rolls to the shipping carton.

Shelf Life: Two (2) years from the date of manufacture or as expressly certified by 3M.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, please visit www.3M.com/msds or call 1-800-364-3577 or (651) 737-6501.

For Additional Information

In the U.S., call toll free 1-800-235-2376, or fax 1-800-435-3082 or 651-737-2171. For U.S. Military, call 1-866-556-5714. If you are outside of the U.S., please contact your nearest 3M office or one of the following branches:

Australia 61-2-949-89333 tel	Austria 01-86686-298 tel	Brazil 55 19 3838-7876 tel	Canada 800-410-6880 ext. 6018 tel
China 86-21-62753535 tel	Denmark 45-43-480100 tel	France 0810-331-300 tel	Germany 02131-14-2344 tel
Hong Kong 852-2806-6111 tel	India 1-800-425-3030 tel (inside country only)	Italy 02 7035-3423 tel 02 7035-2162 fax	Japan +81 3 3709 8165 tel
Korea +82 2 3771 4114 tel	Malaysia 60 3 7806 2888 tel	New Zealand 64-9-477-4040 tel	Netherlands 31-71-5-450-272 tel
Philippines 63-2-588-9100 tel	Singapore 65-6450-8888 tel	South Africa 11-922-9111 tel	Spain 34-91-321-6000 tel
Switzerland 01-724-9114 tel	Taiwan +88 62 2704 9011 tel	Thailand 66-2260-8577 tel	United Kingdom (0) 161-237-6174 tel

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

This product was manufactured under a 3M quality standard registered under AS9100 standards.



Aerospace and Aircraft Maintenance Division

3M Center, Building 223-1N-14
St. Paul, MN 55144-1000
1-800-235-2376
www.3M.com/aerospace

3M is a trademark of 3M Company.
Please recycle. Printed in U.S.A.
©3M 2013 (4/13) All rights reserved.
60-9700-0382-2

