



# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 10/10/2024 Revision date: 27/08/2024 Supersedes version of: 05/12/2023 Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : MASILLA FIBRA DE VIDRIO  
UFI : H0DY-F88P-J003-YGA8  
Product code : BDS002783BU

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Consumer use, Professional use  
Use of the substance/mixture : Sealants and Isolation

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

CRC Industries Europe B.V.  
Touwslagerstraat 1  
9240 Zele  
Belgium  
T +32(0)52/45.60.11, F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com), [www.crcind.com](http://www.crcind.com)

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11  
Office hours: 9-17h CET

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Warning

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH208 - Contains Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]. May produce an allergic reaction.

Extra phrases

: For professional users only.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Vinyltoluene substance with national workplace exposure limit(s) (BE)	CAS-No.: 25013-15-4 EC-No.: 246-562-2 REACH-no: 01-2119622074-50	10 - <12,5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	EC-No.: 911-490-9 REACH-no: 01-2119979579-10	$\leq 0,5$	Acute Tox. 4 (Oral), H302 (ATE=619 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.
--	---

#### 5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Protective equipment	: Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes.

##### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
Other information	: Dispose of materials or solid residues at an authorized site.

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

Vinyltoluene (25013-15-4)	
Belgium - Occupational Exposure Limits	
Local name	Vinyltoluène (tous isomères) # Vinyltolueen
OEL TWA	246 mg/m <sup>3</sup>
	50 ppm
OEL STEL	490 mg/m <sup>3</sup>
	100 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

#### DNEL and PNEC

Vinyltoluene (25013-15-4)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1,65 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5,82 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0,595 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,03 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0,595 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,319 µg/l
PNEC aqua (marine water)	31,9 ng/l
PNEC aqua (intermittent, freshwater)	3,19 µg/l
PNEC aqua (intermittent, marine water)	0,319 µg/l

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Vinyltoluene (25013-15-4)</b>	
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	32 µg/kg dw
PNEC sediment (marine water)	3,2 µg/kg dw
<b>PNEC (Soil)</b>	
PNEC soil	6,21 µg/kg dw
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	5,92 mg/l
<b>Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	1,4 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	9,8 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,74 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0,5 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,048 mg/l
PNEC aqua (marine water)	0,0048 mg/l
PNEC aqua (intermittent, freshwater)	0,48 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	1,2 mg/kg dwt
PNEC sediment (marine water)	0,12 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,21 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal protection equipment

#### Personal protective equipment symbol(s):



### Eye and face protection

#### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Butyl-rubber protective gloves.

### Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

### Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light pink.
Appearance	: Paste.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 170 °C
Flammability	: Non flammable.
Lower explosion limit	: 1,2 vol %
Upper explosion limit	: 8,9 vol %
Flash point	: 52 °C
Auto-ignition temperature	: 480 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: > 20,5 mm <sup>2</sup> /s at 40 °C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1,8 g/cm <sup>3</sup> at 20 °C
Relative density	: 1,8 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### Other safety characteristics

VOC content : 189 g/l (Cat.II B(b) VOC max 250 g/L)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid temperatures exceeding the flash point.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute toxicity (oral)</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Acute toxicity (dermal)</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Acute toxicity (inhalation)</b>	: Not classified (Based on available data, the classification criteria are not met)

#### Vinyltoluene (25013-15-4)

LD50 oral rat	2321,58 mg/kg bodyweight
LD50 dermal rat	4585 mg/kg
LC50 Inhalation - Rat	> 5,02 mg/l/4h

#### Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

LD50 oral rat	619 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight

<b>Skin corrosion/irritation</b>	: Causes skin irritation. pH: Not applicable
<b>Serious eye damage/irritation</b>	: Causes serious eye irritation. pH: Not applicable
<b>Respiratory or skin sensitisation</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Germ cell mutagenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Carcinogenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Reproductive toxicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>STOT-single exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>STOT-repeated exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Aspiration hazard</b>	: Not classified (Based on available data, the classification criteria are not met)

### MASILLA FIBRA DE VIDRIO

Viscosity, kinematic	> 20,5 mm <sup>2</sup> /s at 40 °C
----------------------	------------------------------------

#### Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Viscosity, kinematic	2519,82 mm <sup>2</sup> /s
----------------------	----------------------------

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

#### Vinyltoluene (25013-15-4)

LC50 - Fish [1]	5,2 mg/l Pimephales promelas
EC50 - Crustacea [1]	1,3 mg/l Daphnia magna
EC50 72h - Algae [1]	4,3 mg/l Raphidocelis subcapitata

#### Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

LC50 - Fish [1]	> 100 mg/l Cyprinus carpio
EC50 - Crustacea [1]	48 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Raphidocelis subcapitata

### 12.2. Persistence and degradability

#### MASILLA FIBRA DE VIDRIO

Persistence and degradability : Not established. No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

#### MASILLA FIBRA DE VIDRIO

Partition coefficient n-octanol/water (Log Kow) : Not applicable

#### Vinyltoluene (25013-15-4)

Partition coefficient n-octanol/water (Log Pow) : 3,35

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### MASILLA FIBRA DE VIDRIO

Results of PBT assessment : Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Additional information : No other effects known






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 3269	UN 3269	UN 3269	UN 3269	UN 3269
<b>14.2. UN proper shipping name</b>				
POLYESTER RESIN KIT	POLYESTER RESIN KIT	Polyester resin kit	POLYESTER RESIN KIT	POLYESTER RESIN KIT
<b>Transport document description</b>				
UN 3269 POLYESTER RESIN KIT, 3, III, (E)	UN 3269 POLYESTER RESIN KIT, 3, III	UN 3269 Polyester resin kit, 3, III	UN 3269 POLYESTER RESIN KIT, 3, III	UN 3269 POLYESTER RESIN KIT, 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F3  
Special provisions (ADR) : 236, 340

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Limited quantities (ADR)	: 5l
Excepted quantities (ADR)	: See SP 340
Packing instructions (ADR)	: P302, R001
Transport category (ADR)	: 3
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: E

### Transport by sea

Special provisions (IMDG)	: 236, 340
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: SP340
Packing instructions (IMDG)	: P302
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Polyester resin kits consist of two components: a base material (flammable liquid) and an activator (organic peroxide), each separately packed in an inner packaging.

### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y370
PCA limited quantity max net quantity (IATA)	: 5kg
PCA packing instructions (IATA)	: 370
PCA max net quantity (IATA)	: 10kg
CAO packing instructions (IATA)	: 370
CAO max net quantity (IATA)	: 10kg
Special provisions (IATA)	: A66, A163
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F3
Special provisions (ADN)	: 236, 340
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: See SP 340
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F3
Special provisions (RID)	: 236, 340
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: see SP340
Packing instructions (RID)	: P302, R001
Transport category (RID)	: 3
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### VOC Directive (2004/42)

VOC content : 189 g/l (Cat.II B(b) VOC max 250 g/L)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

# MASILLA FIBRA DE VIDRIO

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.