

Eaton LE215CC05T

Catalog Number: LE215CC05T

Eaton Cooper Power series loadbreak elbow, 200 A, Std V:15 kV, Max phase-to-ground:8.3 kV, AC 1 min:34 kV, DC 15 min:34 kV, Impulse:95 kV, Max corona:11 kV, Test:Yes, 0.75 inch, 1.08 inch, 19.1 mm, 27.4 mm, #1 AWG, 1/0 AWG, 20 pack



General specifications

Product Name	Catalog Number
Eaton Cooper Power series loadbreak elbow	LE215CC05T
	UPC
	194006010481
Product Length/Depth	Product Height
15.25 in	18 in
Product Width	Product Weight
15.25 in	2.18 lb
Compliances	Certifications
Not Applicable	IEEE 386

defaultTaxonomyAttributeLabel

Type

Loadbreak elbow

AC 1 minute voltage withstand

34 kV

Basic impulse level

95 kV

Cable insulation diameter - max

1.08 in

Cable insulation diameter - min

0.75 in

Solid or compact conductor size

1/0 AWG

Stranded or compressed conductor size

#1 AWG

Current rating

200 A

DC 15 minute withstand

34 kV

Maximum rating phase-to-ground

8.3 kV

Corona voltage level - min

11 kV

Standard pack

20 pack

Standard voltage class

15 kV

Features

Flex Center

Resources

Specifications and datasheets

[Eaton Specification Sheet - LE215CC05T](#)

[Line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia