



PDU10BVHVIEC20F BASIC PDU



Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower PDU10BVHVIEC20F, a 20-outlet (front), 0U vertical rackmount basic power distribution unit (PDU), provides 200/230V 10A output. It distributes power to 16 IEC-320 C13, four IEC-320 C19 receptacles from a single IEC-320 C14 plug with unfiltered electrical pass-through. Designed for datacenters and other electrically demanding applications, the PDU10BVHVIEC20F has rugged, industrial-grade metal housing and a ten-foot AC power cord. It supports vertical, horizontal, and wall mount installation, includes a cord retention tray, and is ETL/RoHS certified. A limited lifetime warranty covers defects in materials and workmanship in the product under normal use and conditions.

TYPICAL APPLICATIONS

- VoIP Phone Systems
- Network Closets
- Data Centers
- Industrial Environments

FEATURES

- Phase: Single
- Amps: 10A
- Volts: 200 - 230 V
- Frequency: 50Hz/60Hz
- Plug type: IEC-320 C14
- Outlets: 16 x IEC-320 C13, 4 x IEC-320 C19
- Outlet location: Front
- Size: 0U Rackmount
- Dimensions (in.): 1.75W x 36H x 1.5D
- Cord length (ft.): 10
- Warranty: Limited Lifetime

SPECIFICATIONS

| INPUT | |
|-----------------------|---------------------|
| Cord Length (ft.) | 10 ft (3.0 m) |
| Input Frequency Range | 50Hz - 60Hz |
| Input Plug Type | IEC-320 C14 |
| Maximum Input Current | 10A (Derated to 8A) |
| Plug Style | Straight |

| OUTPUT | |
|------------------------|-------------------------------------|
| Nominal Output Voltage | 200 - 230 VAC |
| Outlet Type | 4 x IEC-320 C19 16 x IEC-320 C13 |
| Outlets - Front | 20 |
| Outlets - Rear | 0 |
| Outlets - Total | 20 |
| Overload Protection | 10A |

PDU10BVHVIEC20F

BASIC PDU

SPECIFICATIONS

| PHYSICAL | |
|---|--|
| Adjustable Mounting Brackets | 3 sets (L-Short, L-Long, Flat) |
| Color | Black |
| Cord Retention Tray/ Cord Organizers | Yes |
| External Site Ground Pin | Yes |
| Form Factors Supported | Horizontal or Vertical Wallmount Racks Horizontal or Vertical Mount in a Variety of Other Surface Types |
| Material of Construction | Metal |
| Rack Height | OU |
| Style | Rackmount Under-Counter |

| PHYSICAL DIMENSIONS | |
|--|------------------------|
| Physical Dimensions - Width/Height/Depth (cm) | 4.45 x 91.44 x 3.81 cm |
| Physical Dimensions - Width/Height/Depth (mm) | 44 x 914 x 38 mm |
| Physical Dimensions - Width/Height/Depth (in.) | 1.75 x 36 x 1.5 in. |
| Weight (kg) | 1.95 kg |
| Weight (lbs.) | 4.3 lbs. |

| SHIPPING DIMENSIONS | |
|--|--|
| Shipping Dimensions - Width/Height/Depth (cm) | |
| Shipping Dimensions - Width/Height/Depth (mm) | |
| Shipping Dimensions - Width/Height/Depth (in.) | |
| Shipping Weight (kg) | |
| Shipping Weight (lbs.) | |

| ENVIRONMENTAL | |
|-----------------------------|------------------------------|
| Operating Elevation | 0 - 10,000 ft (0 - 3,048 m) |
| Operating Relative Humidity | 0 - 95% (non-condensing) |
| Operating Temperature | 32 - 95 °F (0 - 35 °C) |
| Storage Elevation | 0 - 50,000 ft (0 - 15,239 m) |
| Storage Temperature | 5 - 113 °F (-15 - 45 °C) |

| CERTIFICATIONS | |
|----------------|--------------------------------|
| Environmental | RoHS Compliant |
| Safety | ETL (test followed UL 60950-1) |

| WARRANTY | |
|------------------|---------------------------|
| Product Warranty | Limited Lifetime Warranty |