



CSP606T | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Professional Surge Protector CSP606T from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and other consumer electronics. The CSP606T provides 1,350 joules of protection and 6 surge-protected outlets. Data line protection occurs with RJ11 ports for telecommunication devices (phones, faxes, modems, and DSL lines).

Features of the CSP606T include automatic shutdown, data line protection, power cord (6 ft.), right-angle plug with 45° offset, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. The CSP606T comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 1,350 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 6 NEMA 5-15R (surge-protected)
- Power cord: 6 ft
- Color: Black
- Data line protection: Telephone, DSL, Fax
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$75,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	6 - NEMA 5-15R
Outlets - Total	6
USB Charge Port	No
USB Charge Port Amperage	None

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,350 J

CSP606T

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - WxHxD (cm)	4.57 x 3.05 x 21.34 cm
Physical Dimensions - WxHxD (mm)	46 x 30 x 213 mm
Physical Dimensions - WxHxD (in.)	1.8 x 1.2 x 8.4 in.
Weight (kg)	0.41 kg
Weight (lb)	0.90 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	33.66 x 5.89 x 11.76 cm
Shipping Dimensions - WxHxD (mm)	336.55 x 58.93 x 117.6 mm
Shipping Dimensions - WxHxD (in)	13.25 x 2.32 x 4.63 in.
Weight (kg)	0.68 kg
Weight (lb)	1.50 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363
WARRANTY	
CEG Amount	\$75,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty