Specifications





# APC Back-UPS Pro, 1500VA, Tower, 120V, 10 NEMA 5-15R outlets, AVR, LCD

BX1500M

#### Overview

Lead time

Usually in Stock

### Main

wam	
Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	900 W
Rated power in VA	1500 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Battery Type	Lead-Acid battery

### **Batteries & Runtime**

Run Time	View Runtime Graph 🖾
Efficiency	View Efficiency Graph □
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	1
Battery Charge Power (Watts)	11 W rated
Extendable Run Time	0
Replacement battery	APCRBC124

### General

Provided equipment	User Manual USB cable RCBO
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

# Physical

Height	9.8 in (25 cm)
Width	3.9 in (10 cm)
Depth	15.04 in (38.2 cm)
Net Weight	24.3 lb(US) (11 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

# Input

Input Frequency	60 Hz +/- 3 Hz
Efficiency at full load	88139 V
Maximum Input Current per Phase	12 A
Switching current capacity	15 A

# Output

Max Configurable Power (Watts)	900 W
Output Frequency (sync to mains)	60 Hz sync to mains
Тороlоду	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	1500 VA
Transfer Time	8ms typical : 10 ms maximum

# Conformance

Product Certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
Equipment protection policy	Lifetime : \$250000

#### Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5104 °F (-1540 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.00000000015240.000000000 m)
acoustic level	45 dBA
Online Thermal Dissipation	67.6 Btu/h

### **Communications & Management**

Control panel

Multi-function LCD status and control console

Alarm

Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### **Surge Protection and Filtering**

Surge energy rating	789 J
Filtering	Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in
Data line protection	Coaxial cable for CATV/SATV/modem/audio-video

## Ordering and shipping details

GTIN

731304331780

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.7 in (34.8 cm)
Package 1 Width	19.3 in (49.1 cm)
Package 1 Length	8.9 in (22.7 cm)
Package 1 Weight	28.0 lb(US) (12.7 kg)
SCC14	10731304331787

### **Contractual warranty**

Warranty

3 years repair or replace

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



#### **Resource performance**

Energy Efficient Product

Take-Back Program Available

#### Well-being performance

Mercury Free

Rohs Exemption Information

#### **Environmental Certifications**

Energy Star®

ENERGY STAR UPS V2.0 (USA)

Yes

#### **Certifications & Standards**

California Proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"
Circularity Profile	End of Life Information
Environmental Disclosure	Product Environmental Profile
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration

**Technical Illustration** 

Dimensions



#### Offer Marketing Illustration

#### Product benefits / Features







Image of product / Alternate images

Alternative





