# CyberPower

# MP1096SSW MULTI-PACK SOLUTION

## Power, surge protection and USB charging solutions for home and office electronics

The Cyberpower MP1096SSW combo pack comes with one 10-outlet surge protector strip with USB, one five-outlet surge protector strip with USB, and one three-outlet wall-tap with USB.

### TYPICAL APPLICATIONS
- Consumer Electronics
- Personal Computers
- Chargers

### FEATURES - 10-OUTLET SURGE PROTECTOR
- AC Outlets: 10
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 3600 Joules
- USB-A Ports: 1
- USB-A Output: 2.4A
- USB-C Ports: 1
- USB-C Output: 15W
- Cord Length: 4 ft.
- Plug Type: NEMA 5-15P
- Plug Style: flat
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: $300,000
- Warranty: 1-Year Limited Warranty

### FEATURES - 5-OUTLET SURGE PROTECTOR
- Surge suppression: 500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 5
- Total USB Output: 15W
- USB-C charge ports: 1
- USB-C charge output: 15W
- USB-A charge ports: 1
- USB charge output: 2.4A
- Power cord length: 4 ft
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Circuit breaker: 15 A
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: $25,000

### FEATURES - 3-OUTLET WALL-TAP
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 3 NEMA 5-15R
- USB-A charge ports: 4 (4.2-Amp)
- Lighted USB ports: Yes
- Warranty: 1-Year Warranty

# MP1096SSW
# MULTI-PACK SOLUTION

## SPECIFICATIONS

| | 10-OUTLET | 5-OUTLET | WALL-TAP |
|---|---|---|---|
| **INPUT** | | | |
| Plug Type | NEMA 5-15P | NEMA 5-15R | NEMA 5-15P |
| Plug Style | Flat | Right Angle, 45° Offset | Wall-tap |
| Cord Length | 4 ft. | 4 ft. | Wall-tap |
| **OUTPUT** | | | |
| Outlet Type | NEMA 5-15R | | |
| Outlets - Total | 10 | 5 | 3 |
| Output Voltage | 5 VDC | | |
| USB Charge Ports | 1 USB-A, 1 USB-C | 1 USB-A, 1 USB-C | 4 USB-A |
| USB-A Charge Port Output | 2.4 A | 2.4 A (shared) | 4.2 A |
| USB-C Charge Port Output | 15 W | 15 W | 3.4 A |
| **SURGE PROTECTION & FILTERING** | | | |
| Surge Suppression | 3,600J | 500J | |
| Clamping Voltage | 600V (H-N, H-G, N-G) | 800V (H-N) | |
| Response Time | <1 Nanosecond | | |
| EMI/RFI Filtration | Yes | Yes | |
| Auto Shutdown (Safe Fail) | Yes | Yes | No |
| **INDICATORS** | | | |
| LED Indicators | Protected Grounded | | |
| **PHYSICAL** | | | |
| Color | White | | |
| Keyhole Mounting Slots | Yes | Yes | Wall-tap |

| | 10-OUTLET | 5-OUTLET | WALL-TAP |
|---|---|---|---|
| **DIMENSIONS** | | | |
| Product Dimensions (Width/Height/Depth) cm | 9.4 x 4.09 x 28.04 cm | 4.55 x 3.81 x 24.79 cm | 11.3 x 8.94 x 4.9 cm |
| Product Dimensions (Width/Height/Depth) mm | 94 x 41 x 280 mm | 45 x 38 x 248 mm | 113 x 89 x 49 mm |
| Product Dimensions (Width/Height/Depth) in | 3.7 x 11.61 x 11.04 in. | 1.79 x 1.50 x 9.76 in. | 4.45 x 3.52. x 1.93 in. |
| Shipping Dimensions (Width/Height/Depth) cm | 17.78 x 12.7 x 35.56 cm | | |
| Shipping Dimensions (Width/Height/Depth) mm | 177.8 x 127.0 x 355.6 mm | | |
| Shipping Dimensions (Width/Height/Depth) in | 7 x 5 x 14 in. | | |
| Shipping Weight (kg) | 1.45 kg | | |
| Shipping Weight (lbs.) | 3.20 lbs. | | |
| **CERTIFICATIONS** | | | |
| Environmental | RoHS Compliant | | |
| Safety | UL1363 UL1449 4th Edition UL1310 cUL | UL1449 3rd Edition UL1363 UL1310 FCC cUL DOE VI | UL498a 1310 cULI FCC DOE VI |
| **WARRANTY** | | | |
| Product Warranty | One-Year Limited Warranty | | |
| Connected Equipment Guarantee | Lifetime | Lifetime | |
| CEG Amount | $300,000 | $25,000 | |