

Traditional Flush 2X2 FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

2X2 Flush FRPT, One-Piece Units (PT2X2FIT)

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Poke-Through Non-metallic Cover	Black/Aluminum Black/Aluminum Black Gray Black Gray	PT2X2ALU3 PT2X2IGALU3 PT2X2BL PT2X2GY PT2X2IGBL* PT2X2IGGY*	2X2 Poke-Through	Black/Brass Brass Finish/Brass Black/Brass Brass Finish/Brass	PT2X2BRS3 PT2X2BRS PT2X2IGBRS3* PT2X2IGBRS*
- Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks - Painted or brushed aluminum flange - Approved for use in the City of Chicago			- Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks - Solid brass flange - Approved for use in the City of Chicago		

Note: *Includes pre-wired 20A isolated ground Style Line® decorator duplex receptacle.

2X2 Flush FRPT, Two-Piece Units

Description	Catalog Number
Multi-Channel Through-Floor Fitting with (1) ¼ in. EMT stem with junction box for power and (2) ½ in. EMT stems for low voltage.	PT2X2FIT
	Specifications: 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) - For 2¼ in. to 7 in. floor thickness - UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area - Approved for use in the City of Chicago

Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Service Fitting Non-metallic Cover/ Aluminum Flange	Black/Aluminum Black Gray	PT2X2SFALU3 PT2X2SFBL PT2X2SFGY	2X2 Service Fitting Non-metallic Cover/ Brass Flange	Black/Brass Brass Finish/Brass	PT2X2SFBRS3 PT2X2SFBRS
- Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks - Painted or brushed aluminum flange			- Pre-wired 20A Style Line® decorator duplex receptacle and (2) Category 6 data jacks - Solid brass flange		

Accessories

Description	Color/Material	Catalog Number	Description	Color/Material	Catalog Number
Non-metallic Replacement Covers	Brass Finish Black Gray	PT2X2CBRS PT2X2CBL PT2X2CGY	Closure Plug Textured aluminum plug seals 3 in. core hole when FRPT is no longer required and is removed. Maintains the floor's 1 – 4 hour fire rating. UL Listed and CSA Certified.	Gray	FRP250
					

Note: See page Q-43 for technical information.