



# Traverse®

48" x 72-1/4" Vikrell shower back wall  
72522100



## Features

- Tongue-and-groove modular design allows for easy installation during any phase of construction
- Modern subway tile design
- Full-length shelf provides generous storage
- Easy-to-clean, durable high-gloss finish

## Material



- Compression molded from our exclusive solid Vikrell® material

## Installation

- Pro4™ installation system features a two-piece back wall design, enabling one-person handling and installation
- Alcove
- Caulk-free installation
- Must be installed with Guard+ 7232 series shower base and Traverse subway tile 7250 series end wall set

## Recommended Products/Accessories

- K-23733 Vikrell® cleaner
- 1506D-48 Framed pivot shower door
- 581075-48 Frameless sliding shower door
- 547808-48 Frameless sliding shower door
- 5475-48 Frameless sliding shower door
- 5477-48 Frameless sliding shower door
- 5485-48 Frameless sliding shower door
- 5970-46 Framed sliding shower door
- 5970-48 Framed sliding shower door
- 5976-48 Framed sliding shower door
- 5977-48 Framed sliding shower door
- 5960-46 Framed sliding shower door
- 5965-46 Framed sliding shower door
- 5960-48 Framed sliding shower door
- 1500D-48 Framed pivot shower door
- 1505D-48 Framed pivot shower door
- SP1506D-48 Framed pivot shower door
- 1530D-48 Framed pivot shower door
- 1535D-48 Framed pivot shower door



## Codes/Standards

- CSA B45.5/IAPMO Z124
- ASTM E162
- ASTM E662

## STERLING® Vikrell® or Acrylic Baths and Shower Bases Ten-Year Limited Warranty

See website for detailed warranty information.



**Traverse®**  
48" x 72-1/4" Vikrell shower back wall  
**72522100**

No image available.

This product is a component and not intended to be a standalone installation.

### Technical Information

All product dimensions are nominal.

Installation:	Three-wall alcove
Drain location:	Center
Weight:	39.3 lbs (17.8 kg)
Maximum door height:	72" (1829 mm)
Maximum door width:	44-9/16" (1132 mm)

### Notes

Install this product according to the installation instructions.