

Multi-Conductor Shielded, Plenum NEC Type CMP and/or CL3P

**Multi-Conductor
Shielded, Plenum
NEC Type CMP and/or CL3P**

Security and Alarm Cable



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded or solid bare copper per ASTM B-3, B-8 and B-291

Category Insulation Description:

- Premium-grade, color-coded Flexguard® PVC

Shield:

- Overall Flexfoil® polyester supported aluminum foil Stranded tinned copper drain wire

Category Jacket Description:

- Premium-grade natural Flexguard® PVC Sequential footage markings to facilitate installation Temperature range: 0°C to +75°C Ripcord available upon request

Applications:

- Power limited control circuits
- Wiring of the following systems:
 - Intercom
 - Security
 - Audio
 - Background music
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725 Type CL3P (UL: 75°C, 150V)
- NEC Article 800 Type CMP (UL: 75°C, 300V)
- Designed to meet NFPA 262 Flame Test

PART NUMBER TABLE

Part#	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
G111802	18	2	.008"	.015"	.164"	20.5
G111803	18	3	.008"	.015"	.153"	27.5
G111804	18	4	.008"	.015"	.169"	34
G111806	18	6	.010"	.015"	.204"	48.1
G111808	18	8	.010"	.015"	.264"	61
G111810	18	10	.006"	.015"	.264"	5.3
G111812	18	12	.006"	.015"	.273"	86.1
G111602	16	2	.006"	.015"	.154"	28.5
G111603	16	3	.006"	.015"	.190"	28.5
G111604	16	4	.006"	.015"	.181"	49.6

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC