



Sandstorm™ reflects the captivating layers of sandstone in a glazed porcelain tile. High-definition printing enables natural-looking color variation, veining and fissure lines for which natural stone is known.

SANDSTORM™

Glazed Porcelain



FLOOR / WALL

RESIDENTIAL

COMMERCIAL

INDOOR

OUTDOOR



Kalahari

Sizes



12" x 24"
11.81" x 23.62"

Thickness

9.8mm

Faces

16

Finish

Matte

Edge

Pressed

Grout Joint Recommendation

3/16"

Testing

Abrasion Resistance
C1027

Breaking Strength
C648

Chemical Resistance
C650

Water Absorption
C373

DCOF ANSI
A1371

Scratch Hardness
MOHS

Shade Variation
Rating

Results*

III

≥300 lbf

Resistant

≤0.50%

≥0.50

7

V2

Product and Installation Details | ANSI A108.02
Section 4.3.8.2 - For running bond/brick joining patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.