

MINI INCH FLUORESCENT UNDER CABINET

WARNING: RISK OF FIRE AND ELECTRICAL SHOCK.

DIRECT WIRE FLUORESCENT FIXTURE INSTALLATION

CAUTION: Read All Instructions Carefully for Safe Operation and Installation.

1. Exercise care when installing fixture to avoid cuts or abrasions.
2. Before installation TURN OFF electricity to main circuit breaker or fuse box.
3. Consult your local building code for approved wiring and installation requirements.
4. The fixture must be used on a 120 Volt, 60Hz, protected circuit.
5. If fixture is turned on from a wall switch, make sure that the black AC supply wire is connected to the wall switch. Do not connect the white AC supply wire of the fixture to the switch.
6. Ensure that no bare wires are exposed outside of the wire nuts.
7. Be certain that the wire nuts are tight.

INSTALLATION PROCEDURE

1. Remove the lens/diffuser by lightly pressing the front edge while lifting. (See Fig. 1)
2. Rotate fluorescent lamp and remove it from the fixture, if previously installed.
3. Remove wireway cover by removing the nuts or screws.
4. Check fixture wiring for cuts or loose connections which may have occurred during shipment. If any are found, they must be repaired before proceeding with the installation.
5. Carefully remove the knockout, insert the connector with the threaded end inside the fixture and tighten the nut. Install cable. Tighten the two screws on connector after wiring is complete.
6. Connect AC supply black wire to black wire of the fixture and secure them with a wire nut. (See Fig. 2)
7. Connect AC white wire to white wire of the fixture and secure them with a wire nut.
8. Connect AC supply ground (green or copper) wire to ground terminal fixture and secure with nut. (Refer to Fig. 2) The fixture must be grounded to avoid possible electrical shock. If your electrical system contains no grounding (green or copper) wire, you should consult a qualified electrician.
9. Install the wireway cover, tighten nuts and ensure all wires and connections are sealed properly inside the fixture cover.
10. Mount the fixture securely on a surface which is capable of supporting the fixture.
11. Install lamp(s) and rotate them to seat properly.

