Porcelain Stone®

Available Colors



JAV01 ▶ Two Sugars



JAV03 ▶ House Blend



JAV05 ▶ French Press



JAV02 ▶ Flat White



JAV04 ▶ Fresh Ground

Features and Benefits

- Striations of crema and bold neutrals present a product line that is steeped in versatility.
- Color and graphics blend to perfection in 5 tones, sized perfectly in 12 x 24 to suit the superior tastes of any design barista
- Available with bullnose, cove base, and 2 x 2 mosaics
- Competitively priced for exceptional value
- · Cross-Sheen finish for easy cleaning
- Made in the USA

Porcelain Stone®

Available Mosaics



JAV01 ▶ Two Sugars 2 x 2 Mosaics



JAV02 ▶ Flat White 2 x 2 Mosaics



JAV03 ► House Blend 2 x 2 Mosaics



JAVO4 ▶ Fresh Ground 2 x 2 Mosaics



JAV05 ▶ French Press 2 x 2 Mosaics



Porcelain Stone®

Sizes (Shown in JAV02)





2 x 2 Mosaics UPS Finish (Mounted on an 12 x 12 sheet.)

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum _____

order and quick fulfillment.
See website for more details and sizes.



>>> Crossville® Sample Express

Complimentary Samples are available at CrossvilleInc.com/products/java-joint/

Samples may also be ordered through customer service by email or phone.

Sample fulfillment & Help Line Samples@CrossvilleInc.com 1800 221.9093

Loose Samples for Architects & Designers

Loose Tile Samples

Sizes may vary depending on product series

Max. of 4 large field tile per order

Replacement Chips for PSS Rack Max. of 5, 2 x 2 chips per color

Standard Shipping UPS Ground

Sizes & Finishes

4	Field Tile		Available in all colors	
	Nominal (in)	Actual (in)	Thickness (in)	Finish
	12 x 24	11-13/16 x 23-13/16	3/8	UPS

Crossville recommends a grout joint of 3/16 inch.

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicate tile is rectified

Mosaics	4	Available in all colors	
Nominal (in)	Actual (in)	Thickness (in)	Finish
2 x 2 Mosaic	11-3/4 x 11-3/4	3/8	UPS

*Mounted on 12 x 12 sheet

Coordinating Trim

Nominal (mm)	Actual (in)	Thickness (in)	Finish
4 x 24 Single Bullnose	3-13/16 x 23-13/16	3/8	UPS
6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	UPS



Product Performance


· · · · · · · · · · · · · · · · · · ·		
Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS 0.42 - 0.52	AcuTestsm
-----------------	-----------

Shade & Texture Index

Java Joint has a shade variation of V2.



V1 Uniform appearance **V2 Slight Variation**

V3 Moderate Variation
V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.



Crossville, Inc.

PO Box 1168 Crossville, TN 38557 **Phone** 931.484.2110 **Fax** 931.456.2956

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Recommended Use

Java Joint is recommended for interior floors, walls, counter tops and exterior walls in both residential and commercial applications. If offset pattern is required for tiles 18 inches or longer, Crossville® recommends an offset of not greater than 33%. See CrossvilleInc.com for detailed installation instructions.

Environmentally Conscious

Java Joint contains a minimum of 4% pre-consumer recycled content and is manufactured by Crossville® using processes that recycle nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit CrossvilleInc.com/green.



Care and Maintenance

Regular cleaning is the best way to keep Java Joint tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at CrossvilleInc.com.

Our Warranty

Crossville Inc guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.



National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc. com for the latest, most accurate information.



Trade Organizations











Environmentally Aware







