

APPLICATIONS



Versatile Control: lighting, signs, pumps, motors, fans, heating, and air-conditioning, security systems.



FEATURES

- **AUTOMATIC** input voltage detection
- 20 events for programs
- Automatic Daylight Savings adjustment
- Power Outage Backup: **SUPERCAPACITOR** no batteries to replace
- **2-in-1** DPST Contacts — also use as SPST
- **RED INDICATORS** — Red for load status
- 40 AMP contact
- Manual Override ON & OFF

SPECIFICATIONS

MULTI-VOLTAGE INPUT:

120/208-240/277VAC
(automatic detection)

OPERATING TEMPERATURE:

-40°F to +149°F (-40°C to +65°C)

ENCLOSURE:

Indoor/Outdoor NEMA 3R polycarbonate



E/EW/EWZ
E103B: 24 HOUR CONTROL
EW103B: 7 DAY CONTROL
EWZ103: 7 DAY ASTRO

**DETECTS
INPUT
VOLTAGE
AUTOMATICALLY!**

**ACCURATE TO
THE MINUTE!**



RATINGS

40A General Purpose @ 120-277VAC
40A Inductive @ 120-277VAC
30A Ballast @ 120VAC
20A Ballast @ 208-277VAC
15A Tungsten @ 120VAC
1HP @ 120VAC
1 1/2 HP @ 208VAC
2HP @ 240 - 277VAC
720VA Pilot Duty @ 120-277VAC
30A Resistive @ 28VDC