

Earthenware



Colors



Cirrus
VTL EWCI



Cumulus
VTL EWCU



Stratus
VTL EWST




Nimbus
VTL EWNl

Sizes



24" x 48" x 9mm Rectified



12" x 24" x 9mm
Rectified

EARTHENWARE

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" Rectified	23.62" x 47.24"	9.00mm	Matte/Natural
12" x 24"	11.81" x 23.62"	9.00mm	Matte/Natural
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
9" x 10" Split Hex Mosaic	8.66" x 10.24"	Matte/Natural
2" x 2" Mosaic	11.81" x 11.81"	Matte/Natural
3" x 24" Bullnose	2.83" x 23.62"	Matte/Natural
6" x 12" Cove Base	5.91" x 11.81"	Matte/Natural
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	≥350lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	>0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤0.5%
Certifications	Greenguard VOC Free HPD EPD
Country of Origin	USA
Shade Variation Code	V3



V3 Moderate Variation



DCOF: >0.42



Made in USA



Water Absorption: ≤0.5%



Frost Resistant



Greenguard
VOC Free, HPD & EPD



Recommend an offset
pattern ≤33%

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Porcelain



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
SURFACES
COMMERCIAL