



Technical Sheet

WALL-MOUNTED REFRIGERATED BOTTLE FILLER

- PGN8EBF

Suggested Specification

Model PGN8EBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Electronic bottle filler shall include contactless activation and laminar flow. Model PGN8EBF shall be surface mount in design. Plastic bottle filler components contain Freshshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	• High efficiency cooling system
	• Contactless activation
	• Built-in 100 micron strainer stops particles before they enter the waterway
	• Stainless steel with heavy duty galvanized steel frame
	• Waterways are lead-free in materials & construction
	• Built-in filter monitor and bottle counter
	• Ample space within the bottle filler cabinet to add filtration
	• Access through the side of the bottle filler cabinet for clean and easy replacement of filters

Filtration:	Option to add filtration to bottle filler cabinet
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor
Mounting Type:	Wall Mounted
Chilling Option:	8.0 gph
Full Load Amps:	4.6
Rated Watts:	460
Dimensions (D x W x H):	12.7" x 17.9" x 36.8"
Approx. Net Weight:	56 lbs
Installation Location:	Indoor



Installation

- Prior to roughing in, consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket

Options

- OASIS VersaFilter

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each bottle filler; sample available upon request.

Export Warranty

One year on component parts. Detailed warranty certificate enclosed with each bottle filler; sample copy available upon request.

Compliance

- Certified to UL 399 and CAN/CSA C22.2 No. 120
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- Complies with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Technical drawing of a wall-mounted unit, showing three views: front, top, and side. Dimensions are provided in inches and millimeters.

Front View Dimensions:

- Overall width: 12.70 [322.6]
- Width of main panel: 11.50 [292.1]
- Height of main panel: 10.38 [263.7]
- Activation height: 5.43 [137.8]
- Overall height: 50.06 [1271.6]
- Height from wall to top of unit: 13.25 [336.6]
- Height from wall to bottom of unit: 21.25 [539.8]
- Height from wall to top of handle: 17.00 [431.8]
- Height from wall to bottom of handle: 16.50 [419.1]
- Height from wall to top of electrical outlet: 14.26 [362.3]
- Height from wall to bottom of electrical outlet: 17.53 [445.1]
- Height from wall to top of water supply: 17.00 [431.8]
- Height from wall to bottom of water supply: 16.50 [419.1]
- Height from wall to top of waste stub: 14.26 [362.3]
- Height from wall to bottom of waste stub: 17.53 [445.1]
- Height from wall to top of electrical outlet: 14.26 [362.3]
- Height from wall to bottom of electrical outlet: 17.53 [445.1]
- Height from wall to top of water supply: 17.00 [431.8]
- Height from wall to bottom of water supply: 16.50 [419.1]
- Height from wall to top of waste stub: 14.26 [362.3]
- Height from wall to bottom of waste stub: 17.53 [445.1]

Top View Dimensions:

- Overall width: 17.87 [453.9]

Side View Dimensions:

- Overall depth: 1.00 [25.4]
- Depth of main panel: 1.50 [38.1]
- Depth of handle: 1.00 [25.4]
- Depth of electrical outlet: 1.00 [25.4]
- Depth of water supply: 1.00 [25.4]
- Depth of waste stub: 1.00 [25.4]
- Depth of electrical outlet: 1.00 [25.4]
- Depth of water supply: 1.00 [25.4]
- Depth of waste stub: 1.00 [25.4]
- Depth of electrical outlet: 1.00 [25.4]
- Depth of water supply: 1.00 [25.4]
- Depth of waste stub: 1.00 [25.4]

Other Dimensions:

- 11/4 IPS WASTE OPTIMUM LOCATION STUB OUT 1[25] INCH
- 3/8 WATER SUPPLY OPTIMUM LOCATION STUB OUT 1[25] INCH
- AIR FLOW
- ELECTRICAL OUTLET OPTIMUM LOCATION
- WALL LINE

1. TRAP, STOP VALVE AND ELECTRICAL OUTLET NOT FURNISHED.
2. ALLOW 4 INCHES [102MM] MIN. PER SIDE FOR VENTILATION.
- *3. RECOMMENDED ADULT BARRIER FREE HEIGHT INSTALLATION SHOWN. REDUCE HEIGHT BY 3 INCHES FOR INSTALLATIONS USED PRIMARILY BY CHILDREN AGES 12 AND YOUNGER. UNIT SHALL ALSO HAVE A MINIMUM CLEAR FLOOR SPACE 30[760] BY 48[1220]. ADJUST VERTICAL DIMENSIONS AS REQ'D TO COMPLY WITH FEDERAL, STATE, AND LOCAL CODES.
4. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.



1-800-646-2747