SSHAK-3812

SnapStak® Hanger Kit for 3/8 in RET cable



Product Classification

Brand	SnapStak®
Product Type	Hanger kit

Dimensions

Nominal Size	3/8 in
Compatible Diameter, maximum	8.890 mm | 0.350 in
Compatible Diameter, minimum	7.110 mm | 0.280 in
Height	41.00 mm | 1.61 in
Length	66.00 mm | 2.60 in
Width	22.80 mm | 0.90 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)

General Specifications

Hanger Type	Snap-in hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Ordering Note	CommScope® non-standard product
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degredation	=500 hours in salt spray chamber

©2019 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: March 7, 2019

SSHAK-3812

Mounting	3/8 in (M10) drilled cable ladder
Vibration Survival	=4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

Packed Dimensions

Height	32.5 cm | 12.8 in
Length	15.5 cm | 6.1 in
Shipping Weight	1.40 kg | 3.09 lb
Width	13.5 cm | 5.3 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

©2019 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: March 7, 2019