

MaxColor™ Series MC-TX2

Just Add
Power
AV over IP Solutions

4K60 Encoder with KVM Support, Audio Return Channel & Fiber Port Connection



The MaxColor™ 4K60 MC-TX2 Encoder adds powerful new capabilities, including KVM support, Audio Return Channel (ARC), and an integrated fiber port. It natively supports 4K60Hz input and output, enabling playback of High Dynamic Range content—such as Dolby Vision and HDR10+.

MaxColor Series 2 allows high-bandwidth video to be distributed over a standard 1Gb managed network using existing Cat5e/Cat6 cabling, or over fiber, giving you the flexibility to choose the infrastructure that best fits your project.

MaxColor™ Series MC-TX2

Just Add
Power
AV over IP Solutions

Video

Maximum Input	4096x3840, 60fps, 36-bit color depth, YUV422 4096x3840, 60fps, 24-bit color depth, YUV444 2560x1440, 60fps 2560x1080, 120fps 1920x1080, 60fps, 36-bit color depth, YUV444
Maximum Output	4096x3840, 60fps, 36-bit color depth, YUV444
Dynamic Range	SDR, HLG, HDR10, HDR10+, Dolby Vision
HDMI Standard	HDMI 2.0b/2.1
EDID Management	Default, Built-in, Custom, and Captured

Audio

Supported Audio	All Audio Formats Audio Return Channel (ARC)
Stereo Audio Maximum Sample Rate	192kHz

Compliance

Certification	FCC/CE/ROHS/RCM
HDCP Compliance	2.2, 2.3

Endpoint Control

Endpoint Control Features	Serial Pass-through, Serial over IP, IR over IP, and CEC over IP
--------------------------------------	---

Image Pull

Format & Video Sub-stream	JPEG & mJPEG
Maximum Framerate	30 fps

USB (KVM)

USB Standard	USB 2.0
USB Features	Keyboard, Mouse, Touchscreen, Gaming Controller or Joystick, USB Flash Drive, PTZ Camera Control Devices, Webcam Video Devices, and Microphones

Network

Maximum Bandwidth	850 Mbps
Average Bandwidth	850 Mbps
Video Codec	Proprietary AGIC-G3 Visually Lossless
Audio Codec	Proprietary I2S Lossless
Encryption	AES-256 Hardware Based Crypto Engine

MC-TX2 Specifications

Dimensions	202 x 30 x 131 mm 8.0 x 1.2 x 5.2 inch
Weight	0.57 kg / 1.3 lb
Ports	RJ-45 (1Gb Network) Shared SFP (1Gb Network) HDMI In 3-pin Euroblock Stereo Out 3-pin Euroblock IR Out 3-pin Euroblock 2-Way RS232
Power Supply	5V-18V, 10W 5.5mm/2.1mm, positive tip
Operating Temp	0-60 °C / 32-140 °F
Device Type	Encoder
POE	IEEE 802.3af (15.4W)
Current Version Release Date	


Previous Hardware Version:

H1: Manufacture Dates: February 2023 - April 2026
See page 4 for specifications.


MaxColor™ Series MC-TX2

Just Add
Power
AV over IP Solutions


Front of Device:



Back of Device:



Bottom of Device:



MC-TX2 Previous Hardware Version H1

Manufacture Dates: February 2023 - April 2026

H1 Back of Device:



H1 Bottom of Device:



Specifications

H1 Ports	RJ-45 (1Gb Network) HDMI In 3.5mm Stereo Out 3.5mm IR Out 3.5mm 2-Way RS232	Power Supply (not included)	4.7-23V, 10W 5.5mm/2.1mm, positive tip
Dimensions & Weight	171 x 30 x 127 mm 6.7 x 1.2 x 5.0 inch 0.47 kg / 1.0 lb		

MaxColor™ Series MC-TX2

Just Add
Power
AV over IP Solutions

Need product images for your marketing?

Check out our Sales Partner Resource Page!

www.justaddpower.com/sales-partner-resources/

