

FLUSH SWING HANDLES



Flush Handles are optional for any solid, window or disconnect door greater than 600mm in height, except Voice/Data and Colocation cabinets. They are ergonomically designed to provide style and function in a low profile. The handle is die-cast zinc finished with RAL 9005 textured black polyester powder paint. Provision to add your logo is included. Handle can be installed to rotate either clockwise or counterclockwise.

Handle with Screwdriver Defeater

Enclosure security is provided by the integrated tool-to-open feature that releases the handle when rotated, allowing access to the enclosure.

Handle with Keylock

Keylock feature locks the handle to provide security for the enclosure. When the key is in the unlocked position, the pushbutton releases the handle to provide access to the enclosure. Two keys are furnished.

Handle for Padlock

Padlocking Handle provides security when using up to a 5/16-in. padlock shackle. Pushbutton releases the handle to provide access to the enclosure.

Handle with DIN Profile Provision

DIN Flush Handle is provided with the option to add your DIN profile lock or to accept Hoffman DIN profile lock PDKL (order separately).

BULLETIN: P20

| Catalog Number | Description |
|----------------|----------------------------|
| PFHDF | Flush Handle with Defeater |
| PFHKBL | Keylocking Flush Handle |
| PFHPBL | Padlocking Flush Handle |
| PFHDBL | DIN Profile Flush Handle |

L HANDLE



The L Handle is a stylish option for any solid, window or disconnect door, except Voice/Data or Colocation cabinets. It can be installed to rotate either clockwise or counterclockwise. Handle comes with a bezel, includes keylocking provision and is finished with RAL 9005 textured black polyester powder paint. Two keys are included. The bezel permits your logo to be inserted.

BULLETIN: P20

| Catalog Number | Description |
|----------------|--|
| PLHK | L Handle with 2 keys and logo slot, key code 333 |

FLUSH BEZELS



Bezel with Insert

Can be used on any solid, window or disconnect door when a low-profile, tool-to-open operating mechanism is needed. Bezel is RAL 9005 textured black plastic. Provision to add your logo is included. Flush bezels are provided with screwdriver slot insert. Other key inserts are available to fit the flush bezel (order separately).

Small Bezel with Insert

Can be used in place of the small Flush Swing Handle when a low-profile, tool-to-open operating mechanism is needed. Bezel is RAL 9005 textured black plastic. Provision to add your logo is included. Small flush bezels are furnished with a screwdriver slot insert. Other key inserts are available to fit the small flush bezel (order separately).

BULLETIN: P20, P20S

| Catalog Number | Description |
|----------------|---|
| PFBS | Flush Bezel with Insert |
| PSFBS | Small Flush Bezel with Insert |
| PFBSSS | Large Flush Bezel with Stainless Steel Insert |

KEY INSERTS



Key Inserts are used with Flush Bezels. Optional for any solid, window and disconnect door. Key Inserts are zinc die-cast. A matching key is included.

BULLETIN: P20, P20S

| Catalog Number | Description |
|----------------|--------------------------|
| PKOTM7 | 7-mm triangle |
| PKOTM8 | 8-mm triangle |
| PKOTM65 | CNOMO |
| PKOSM7 | 7-mm square |
| PKOSM8 | 8-mm square |
| PKOGBK3 | Double-bit with 3-mm pin |
| PKOGBK3SS | Double-bit insert |

PADLOCK KIT



The kit adds a padlocking capability to any of the Flush Swing Handles (except for Small Flush Swing Handle). Field modification of the flush handle is required. Includes a stainless steel locking post that will accommodate up to a 5/16-in. padlock shackle.

BULLETIN: P20

| Catalog Number | Description |
|----------------|-------------|
| PFHPK | Padlock Kit |

DIN LOCK INSERTS (FOR DIN PROFILE HANDLE ONLY)



The DIN profile keylock provides keylocking security for the Flush Swing Handle with DIN provision. Includes profile lock and two keys. Order one profile lock for each handle. DIN Lock Kit for PROLINE DataCom doors includes two locks keyed alike with one of 100 different key codes and two keys (master key available). *All DIN Lock Inserts are zinc die-cast.*

BULLETIN: DPY, P20

| Catalog Number | Description |
|----------------|--|
| PKOSLFH | Slotted insert profile cylinder |
| PKOTM7FH | 7-mm triangle insert profile cylinder |
| PKOSM7FH | 7-mm square insert profile cylinder |
| PKOTM8FH | 8-mm triangle insert profile cylinder |
| PKOGBK3FH | Double-bit 3-mm insert profile cylinder |
| PKDL | DIN keylock, 2 keys included, key code 333 |
| PDKLRKPR | DIN Lock Kit for PROLINE DataCom doors |

DIN profile inserts are used with DIN flush swing handles. One key is included (except for slotted insert).

SMALL FLUSH SWING HANDLE



Small Flush Swing Handles are used on smaller doors (doors less than 800mm in height that have two-point latching). Handles are ergonomically designed to provide style and function in a low profile. They can be installed to rotate either clockwise or counterclockwise. The shape of the design provides aesthetic compatibility with the Flush Swing Handles. This handle includes keylocking provision, two keys, provision to add your logo and is furnished in RAL 9005 textured black polyester powder paint.

BULLETIN: P20

| Catalog Number | Description |
|----------------|-------------------------|
| PSHKBL | One handle and two keys |