

## T-REX® BRUTE FORCE® PREMIUM, CO-EXTRUDED CLOTH TAPE WITH EXTREME TENSILE CLOTH

### TYPICAL APPLICATIONS

- For extreme repairs that demand a ferociously strong hold
- Use to bundle, support and haul heavy loads or as an alternative to ropes and chains
- For use on rough or dirty surfaces

### PRODUCT FEATURES

- Super-tough, premium, co-extruded cloth duct tape
- Forge-Link™ Technology extreme tensile cloth offers superior strength, allowing one loop of tape to hold 800+ lbs of weight\*
- High tack, double-thick adhesive sticks to rough and dirty surfaces
- Strong duct tape is too tough to tear by hand
- Durable waterproof backing to withstand extreme weather and reliable performance in temperatures ranging from 32 F to 200 F
- Made using Polybonded CO-EX Technology® that prevents delamination
- Made in USA with Global Materials
- \*1 yard of tape looped to itself; tape not weight rated for towing applications, visit [treatape.com](http://treatape.com) for details

### CONSTRUCTION

Backing: Durable waterproof backing

Adhesive: Natural rubber adhesive

### STANDARD WIDTH

1.88 in

48 mm

### STANDARD LENGTH

25 yd

22.8 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	75 oz/in width	8.21 N/10 mm
Elongation	21%	21%
Service Temperature Range	32 F to 200 F	0 C to 93 C
Tensile	250 lbs/in width	437.8 N/10 mm
Thickness - Nominal	17.0 mils	0.43 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



\*1 yard of tape looped to itself; Tape not weight rated for towing applications, visit [T-RexTape.com](http://T-RexTape.com) for details.