

SUBURB



SUBURB



SUBURB / MURPHY p.24



SUBURB / MONTCLAIR p.19



SUBURB / PINECREST p.12



SUBURB / WESTWOOD p.6

colors

SUBURB / WESTWOOD



SUBURB / PINECREST



SUBURB / MONTCLAIR



SUBURB / MURPHY



Natural in both color and movement, the Suburb collection from Milestone provides a warm, neutral appearance that suits almost any room. Suburb embodies the beauty and character of natural limestone, but with the added durability and benefits of porcelain.





SUBURB / WESTWOOD





SUBURB / PINECREST



18"x18" . 12"x24" / PINECREST



SUBURB / MONTCLAIR





SUBURB / MURPHY



18"x18" / MURPHY

SIZES & SHADE VARIATION

20

sizes:

12"x24"



1096248 Westwood
1096246 Pinecrest
1096249 Montclair
1096246 Murphy


18"x18"



1096253 Westwood
1096252 Pinecrest
1096254 Montclair
1096251 Murphy

mosaics & trim pieces:

12"x12" Mosaic




1096261 Westwood
1096260 Pinecrest
1096262 Montclair
1096259 Murphy

3"x12" Bullnose



1096257 Westwood
1096256 Pinecrest
1096258 Montclair
1096255 Murphy


21



V1

UNIFORM APPEARANCE


Differences among pieces from the same production run are minimal.



V2

SLIGHT VARIATION


Clearly distinguishable differences in texture and/or pattern with similar colors.



V3

MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.










V4

SUBSTANTIAL VARIATION

Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.

technical specifications

		REFERENCE VALUE	DECLARED VALUE	TEST METHOD
	SURFACE ABRASION		V	ASTM C1027
	WATER ABSORPTION	≤0.5%	MEETS REQUIREMENT	ASTM C373
	CHEMICAL RESISTANCE	AS REPORTED	NOT AFFECTED	ASTM 650
	DYNAMIC COEFFICIENT OF FRICTION	≥0.42 WET	MEETS REQUIREMENT	ANSI A137.1
	STAIN RESISTANCE	AS REPORTED	NOT AFFECTED	ASTM C1378
	BREAKING STRENGTH		≥400	ASTM C648
	RESISTANCE TO FREEZE	AS REPORTED	RESISTANT	ASTM C1026



RESISTANT FOR THE HOUSE The product is water-resistant: it stops liquids, body oils, acidic and staining substances from penetrating the tiles. It resists scratches, scuffs and gauges better than any other floor covering. It does not absorb fumes, odors or smoke. It doesn't discolor or fade when exposed to sunlight, or other natural elements. It is completely fire proof. It resists burns and doesn't feed a fire. Its high resistance to abrasive dirt and grime makes it suitable even for heavy-traffic areas of the house such as hallways, entrances, foyers and walkways.

FROST RESISTANT Exceeding the ADA standard requirements, the Milestone product can also be used for outside applications. It stands up to abrupt temperature changes and freezing-thaw cycles. When properly installed according to ANSI A137.1. It's strong enough to be used in exterior applications even in frigid climates. Proper consideration must be given to the anti-slip requirements of the area to be tiled.

ANTI-SLIP The testing conducted on our finished product will guarantee that all of our tiles will have an anti-slip surface so they may be used with total confidence in kitchen and bath applications. The Milestone product is perfect for both home and commercial interiors, such as restaurants, offices, retail stores, etc. Its anti-slip properties provide a safe walking surface in both wet and dry conditions, according to the Americans with Disabilities Act.

HYGIENE/SANATATION & EASY CLEANING The Milestone product doesn't absorb odors or bacteria of any kind. It's easy to clean with a damp sponge, mop, or cloth. For a more intense cleaning, simply use a mild solution of water and a common household detergent. Regular cleaning will stop the growth of germs and bacteria in damp areas such as the bathroom.

• DUE TO THE INHERENT NATURE OF FIRED PORCELAIN TILE, IT IS IMPORTANT TO NOTE THAT THE COEFFICIENT OF FRICTION MAY VARY WITHIN AND BETWEEN PRODUCT RUNS.

packaging

SIZES	METRIC (CM)	THICKNESS (MM)	PIECES PER BOX	SQ.FTPERBOX	WEIGHT PER BOX	BOXES PER PALLET	UOM PER PALLET	WEIGHTPERPALLET*
FIELD TILES								
18"x18"	45x45	9 mm	7	15.75	58.3	32	504	1,865
12"x24"	30x60	9 mm	7	14	51.8	48	672	2,486
MOSAICS AND COORDINATING TRIMS								
3"x12" BULLNOSE	7.5x30	9 mm	12	3	12	168	2,016 pcs	2,016
2"x2" MOSAIC (12"x12")	30x30	9 mm	10	10	37	45	450 pcs	1,665

* WEIGHT PER PALLET DOES NOT INCLUDE PALLET WEIGHT ITSELF.
ALL OTHER SIZES WILL BE PACKAGED AS ORDERED.
PLEASE CONTACT MILESTONE CUSTOMER SERVICE AT 1-877-356-7461 FOR PACKAGING INFORMATION.

MINIMUM GROUT SIZE RECOMMENDED = 5 MM (OR APPROX. 3/16") IF STAGGERED TILE PLACEMENT, WE RECOMMEND USING A 30% OFFSET. IF SPECIFIED BRICK PATTERN WITH 1/2 PATTERN MANDATORY, A BIGGER GROUT IS RECOMMENDED TO HIDE IMPERFECTIONS OF INSTALLATION (MINIMUM 1/4").

- Routine care instructions:
1. Wash with water to remove superficial dirt.
 2. Application of Fila Cleaner® Fila (commercial product) diluted to an average of 1:200 to the surface.
 3. Let the solution sit 5-7 minutes.
 4. Remove the cleaner with a vigorous mechanical cleaning action using common hand cleaning equipment, or a suitable floor-cleaning appliance.
 5. Dry the floor completely.

Note: For desired results, it is particularly important to combine the effect of the detergent with a vigorous mechanical cleaning action.

The products mentioned in these instructions do not officiate any official agreements with any floor cleaning product producers.

CLEANING & MAINTENANCE



CERTIFICATIONS & ACCREDITATIONS

PROGRESSTHATTOUCHESANDINVESTSINTHEENTIRESOCIETY

As an active member of the U.S. Green Building Council, Milestone spreads awareness to the entire American community and encourages a new wave of building solutions inspired by environmentally friendly practices. Using Milestone products for project implementation will positively contribute to obtaining scores and points required for earning the LEED certification (Leadership in Energy and Environmental Design).

ACOMMITMENTTOTHEDEVELOPMENTOFPRODUCTSFORACONSCIOUS BUILDING TRADE

Milestone offers products containing recycled material. The adoption of eco-compatible production systems is one of the design goals produced in the U.S.

TECHNICALDEVELOPMENTTHATCONSIDERSTHENATURAL ENVIRONMENT

Milestone commits to the eco-compatible project and mandates the same to its avant-garde production process, minimizing the negative impact on the environment.

WHY PORCELAIN?

There are many reasons to choose impervious porcelain tile over other floor coverings. It offers the largest array of design options and holds its value the longest in a comparison between the many different flooring options. Porcelain tile offers one of the most durable and least expensive options over the lifespan of the building.

Benefits of Porcelain Tile

- Impervious to water
- Easy to maintain
- Variety of design options
- Environmentally friendly
- Resistant to germs and bacteria
- Fade resistant
- Fire resistant
- Durable - best long-term value vs. other floor coverings

PEI Class 	Heavy traffic In the presence of scratching dirt, in the most severe conditions to which glazed surfaces can be exposed (entryways, work areas, restaurants, exhibitions, shops, and other environments in public or private buildings, and more)
	40% RECYCLED CONTENT

300 International Blvd. Clarksville, TN 37040 | www.milestonetiles.com | 1-877-356-7461

