Sonder



Colors



White VTL S1WH



Beige VTL S1BE



Blue VTL S1BU





Gray VTL S1GY



Green VTL S1GN



Navy VTL S1NV

SONDER

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
3" x 12"	3.00" x 12.00"	8.00mm	Gloss

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Product Characteristics

	GLOSS
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 300lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	N/A
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.5%
Certifications	Carbon Neutral
Country of Origin	USA
Shade Variation Code	V3

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

^{**} These recommendations are not defined by ANSI Standards

Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified



Material Glazed Porcelain





Ready Ship







Request samples.

www.vitisurraces.com samples@vitlsurfaces.com









