


SKINTOP® SLN/SLRN

Strain relief with NPT thread



Complete the installation



SKINTOP®
DIX bushing
page 545



Plugs
page 522



SKINTOP®
GMP locknuts
page 541

SKINTOP® SLN/SLRN is a durable, liquid-tight, easy-to-assemble strain relief cable gland with NPT thread that is universally suited for all types of machinery & equipment, including automation, motion control, process control, and robotics. SKINTOP® SLRN includes reducer bushing.

Approvals



Application advantage

- The heavy duty SKINTOP® design provides great pullout strength and very reliable strain relief
- Superior integrated locking mechanism includes an internal ratchet for vibration-proof protection
- Multi-trapezoidal thread requires just one twist to tighten
- Generous high-quality neoprene bushing provides a liquid-tight and dust-proof hermetic seal

Technical data



Material:

- body: polyamide
- bushing: CR



Color:

black (RAL 9005), UV resistant
gray (RAL 7001)



Locknuts:

add SKINTOP® GMP, page 541



IP Protection:

70 PSI
- seal: IP68, 5 bar
NEMA 1, 12



Temperature range:

- static: -40°C to +100°C
- dynamic: -25°C to +80°C

Part number		Thread	UL status	Clamping range (øF)		Wrenching flats (SW) in	Overall length (C) in	Thread length (D) in	Pack size
black	gray			in	mm				
Standard									
S2138	S1138	NPT ¾"	Recognized	0.138 - 0.315	3.5 - 8	0.748	1.693	0.591	100
S2112	S1112	NPT ½"	Listed	0.197 - 0.472	5 - 12	0.945	1.772	0.591	100
S2134	S1134	NPT ¾"	Listed	0.512 - 0.709	13 - 18	1.299	2.087	0.591	50
S2101	S1101	NPT 1"	Listed	0.748 - 1.000	19 - 25.4	1.654	2.362	0.591	25
Reducer bushing									
S2238	S1238	NPT ¾"	Recognized	0.079 - 0.236	2 - 6	0.748	1.693	0.591	100
S2212	S1212	NPT ½"	Listed	0.157 - 0.354	4 - 9	0.945	1.772	0.591	100
S2234	S1234	NPT ¾"	Listed	0.354 - 0.630	9 - 16	1.299	2.087	0.591	50
S2201	S1201	NPT 1"	Listed	0.551 - 0.984	14 - 25	1.654	2.362	0.591	25

Orders of 2000 pieces or more per item will be bulk packaged unless otherwise requested